


IIS206

IIC015BASKG/M/US-104-DRS/2LED

Inductive sensors



Product characteristics

Inductive sensor

Metal thread M30 x 1.5

Quick disconnect

Operation as 3-wire or 2-wire possible

Increased sensing range

Optical setting aid (2 LED)

gold-plated contacts

Sensing range 15 mm; [f] flush mountable

Electrical data

Electrical design	3-wire DC PNP; 2-wire DC PNP/NPN
Operating voltage [V]	10...36 DC
Current consumption [mA]	10 (24 V)
Protection class	II
Reverse polarity protection	yes

Outputs

Output function	normally open
Voltage drop [V]	< 2.5
Minimum load current [mA]	2; only in 2-wire operation
Leakage current [mA]	< 0.5; only in 2-wire operation
Current rating [mA]	100
Short-circuit protection	yes (non-latching)
Overload protection	yes
Switching frequency [Hz]	100

Monitoring range

Sensing range [mm]	15
Real sensing range (Sr) [mm]	15 ± 10 %
Operating distance [mm]	0...12.1

Accuracy / deviations

Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / aluminium approx. 0.4 / copper approx. 0.3
Hysteresis [% of Sr]	3...15
Switch-point drift [% of Sr]	-10...10

Environment

Ambient temperature [°C]	-25...70
Protection	IP 67

Tests / approvals

IIS206

IIC015BASKG/M/US-104-DRS/2LED

Inductive sensors

EMC	EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 10 V/m EN 61000-4-4 Burst: 2 kV EN 61000-4-6 HF conducted: 10 V EN 55011: class B
-----	---

MTTF	[Years]	1475
------	---------	------

Mechanical data

Mounting	flush mountable
Housing materials	brass white bronze coated; active face: PBT
Weight [kg]	0.14



Displays / operating elements

Output status indication	LED	yellow (4 x 90°)
Setting aid	LED	red

Electrical connection

Connection	M12 connector; gold-plated contacts
------------	-------------------------------------

Wiring



Accessories

Accessories (included)	2 lock nuts
------------------------	-------------

Remarks

Remarks	suitable for PLC type 1 according to IEC 61131-2	
Pack quantity	[piece]	1