



Product Specification

Item: 1

Qty: 2

Description: **NPS 1 MR95HP Standard European Certification**

Service Description:

Direct Operated Regulator: M95H-3063-2590129	Valve Plug Guide Material: 416 SST
Type: MR95HP	Valve Disk Holder Material: 416 SST
Valve Size: NPS 1	Seat Ring Material: 416 SST
Pressure Registration: Internal	Inner Valve Spring Material: 302 SST
Body Material: CF8M SST	Spring Case Bolting Material: SST (B8M Class 2)
NACE: No	Control Spring Part Number: ERCA04295A0
End Connection: NPT	Internal Relief: No
Spring Range: 15 to 100 psi	Vent Location: Over Outlet
Spring Case Material: CF8M SST	Bugproof Vent: No
Spring Case Tapping: 1/4 NPT	Body Tapping(inlet/outlet): None/None
Trim Number: 14	Max Inlet Pressure: 1000 psi (68.9 bar)
Trim Material: 416 SST	Max Outlet Pressure: 550 psi (37.9 bar)
Seat Type: Comp Seat	Temperature Range: 0 to 300 Deg F
Valve Disk Material: FKM	Approximate Shipping Weight(each): 22 lbs (10 kg)
Reduced Port Option: No	Supplemental Attribute: Not App
Diaphragm Material: FKM	Pressure:
PTFE Protector: No	Temperature:
Inlet Pressure Gauge: None (No tap)	Flowing Drop:
Outlet Pressure Gauge: None (No tap)	Shutoff Drop:
Adjusting Screw/Handwheel: Sealed Adjusting Screw/Jam nut	Offset:
ATEX for Regulators: No	Service:
Orifice/Port: 0.631 Inch/16.02 mm	World Area Selections:
Valve Plug Material: Not App	
Product_Service: PSC-2289-91956	European Standard: EN 10204-3.1
Certificate Type: Conformity, Test and Material	
Certificate Description 1: Actual Test Report	Fisher (IPO) Code: T3/M1
Certificate Description 2: Air Test, Seat Leakage, Functional	Supplemental Attribute: Not App
Certificate Description 3: Sub-Supplier Material Certs - Body Only	Product: Regulator
Additional Copy: Not App	