



LAMIFLEX
GROUP

LAMIFLEX - FLEXIBLE PACKAGING

Lamiflex

Flexible packaging



Standard Dimensions and Material Types

Type	W	T	4	C	Form of delivery
Outer surface					= Continuous
= White reinforced paper					Material thickness
Inner surface					= 4 mm
= PE coated craft paper					

Paper/Film Qualities

S: Brown craft paper

T: Brown PE-coated craft paper

D: Dark blue PE-coated craft paper

L: Light blue PE-coated craft paper

W: White, reinforced, PE-coated, UV-stable and seawater-proof paper

R: Brown anti corrosion paper

FB: Blue biaxial orientated cross laminated HDPE modified LDPE film, UV-stable and seawater-proof

FW: White biaxial orientated cross laminated HDPE modified LDPE film, UV-stable and seawater-proof

Supply options

Lamiflex is supplied fan folded on pallets.

Sheets of Lamiflex are also available with a maximum size of 6,10 m x 1,55 m.

Pallet size: Height 0,60 m, Width 1,10 m, Length 1,00 – 6,10 m depending on your chosen Lamiflex-width or sheet size. Printing on the outer surface, e.g. with company logo is available on request, according to quantities.

Type	Core Material	Dimension Width [m]	Dimension Length/pallet [m]	Weight
TS 4C LS 4C	3.2 mm thick hardboard	0.15 – 6.10	155	2.60 kg/m ²
WT 4C WR 4C	3.2 mm thick hardboard	0.15 – 6.10	155	2.75 kg/m ²
FBT 4C FWT 4C FBR 4C FWR 4C	3.2 mm thick hardboard	0.15 – 6.10	155	2.75 kg/m ²
WR 5C FBT 5C	4.2 mm thick hardboard	0.15 – 6.10	114	3.50 kg/m ²
DD 10C TT 10C	8 mm thick softboard	0.15 – 6.10	60	1.90 kg/m ²

For further technical data, see product specific data sheets.
Technical and isometric values are subject to change.