

Scope of supply		
Components*	Description	Qty
Air end	Standard Hibon positive displacement blower in cast iron and steel, type NX12.	1
Inlet	Carbon steel inlet silencer with integrated filter cartridge	1
Outlet	Non return valve, connecting pipe and flexible sleeve	1
Drive	V-BELT/Tooth-belt drive with safety guard	1
Base frame	Base frame in carbon steel with integrated silencer, safety pressure valve, automatic system for belt tensioning, earth connection, anti vibratory pads and anchor bolts.	1
Electric motor	Squirrel cage motor 45 kW – 3000 rpm – IE3 – 415 V- 3phases- 50hz - B3 – IP55 – IE3 Classification - class insulation F / temperature B – cast iron frame – IC 411 self ventilated - terminal box fitted on the top side – 1 set of heaters - tropicalization - Design / construction / painting according to IEC EN60034 norm Brand at choice of Ingersoll rand : Focquet (ABB motor on request with extra cost)	1
Instrumentation	- 1 inlet filter clogging indicator diam.63 - 1 pressure gauge diam. 63 (bar unit) fitted on the enclosure - 1 temperature switch – blower thermal protection (setting point 140°C)	1
Painting	Base unit and blower painted according to our standard specifications: • Alkid Acrylic "galmakyd 55000" with a nominal dry film thickness of 40µm • Acoustic enclosure: epoxy powder 40 µm beige (Munsell 3.6 Y 7.31/2.9) • Blower, frame and silencer: black (RAL 9005) • Drive guard: Red (RAL 3020)	1
Oil	Hibon synthetic lube supplied for first filling	1
Dimensions	Refer to Ingersoll Rand Air Solution Hibon G.A Drawing	1
Packing	Road packaging included (pallet with plastic cover)	
Acoustic enclosure	Indoor acoustic enclosure on palletisable frame with additional ventilation fan 1,1 kW - 415/3/50 Hz - IP55 - IEC standard * Carbon steel sheet panel painted according to Ingersoll Rand standard paint * Self-extinguishing acoustic material: polyurethane foam	1

* Silent Flow packages are made of vendor standard parts