
Profile

- Hollow shaft, max. Ø 14 mm
- Counter with 4 decades and fine reading
- Detent as an option
- Magnifying function for good readability
- Stainless-steel driving shaft as an option
- Axial seal, dustproof and splash-proof
- Clamping plate (see accessories)





Mechanical data

Feature	Technical data	Additional information
Housing	reinforced plastic	
Sight window	plastic	mineral glass as an option
Counter	4 decades, fine reading	
Digit height	~6 mm	
Weight	0.05 kg	

Max. speed

Display (after 1st revolution)	max. speed [rpm]
0010	500 (1500)
0015	500 (1000)
0020	500 (750)
0025	500 (600)
0030	500
0040	375
0050	300
0060	250
0080	180
0100	150

Formula:

$$\text{max. speed} = \frac{15000}{\text{indication after 1st revolution}}$$



Speeds >500 rpm must only be run for short periods.

Ambient conditions

Feature	Technical data	Additional information
Ambient temperature	0 ... 80 °C	

Order

Ordering information

Display	Mounting position				Counting direction
	 02	 04	 06	 07	

Hint: Texts highlighted in orange color are ordering features

Ordering table

Feature	Ordering data		Specification	Additional information
Mounting position	...	A	02, 04, 06, 07	see the icons illustrating the mounting positions
Indication after 1st revolution	...	B	10, 12/5, 15, 17/5, 20, 25, 30, 35, 40, 50, 60, 80, 100	/5 = arithmetical value not displayed
			others on request	
Decimal place	0	C	0 = 0000	
	1		1 = 000.0	
	2		2 = 00.00	
	3		3 = 0.000	
Counting direction	i	D	clockwise ascending values	
	e		counter-clockwise ascending values	
Hollow shaft/diameter	...	E	12.7, 14, 15, 16 in mm	
	...		VA5, VA10, VA14, VA15	stainless steel
	...		RH4, RH6, RH8, RH10, RH12	reducing bushes
Color	0	F	orange RAL 2004	
	S		black RAL 9005	
	GR		gray RAL 7035	
	FR		red RAL 3000	
Seal	OAD	G	without additional seal	
	AD		with axial seal	
	GD		with axial and housing seal	sealing plate not applicable
Detent/hollow shaft	OAR	H	without lock	
	AR		with lock	vibration protection M ~20 Ncm, only with "0" or "S" housing color
Intermediate plate	OZP	I	without intermediate plate	
	ZP		with intermediate plate	not with seal "GD"

Order key

DA04 - [A] - [B] - [C] - [D] - [E] - [F] - A - K - [G] - [H] - [I] - BP - ORP

Scope of delivery: *DA04*

Accessories:

Reduction sleeve RH	*www.siko-global.com*
Clamping plate KP04	*www.siko-global.com*
Clamping plate KPL04	*www.siko-global.com*

subject to technical alteration • 2016/11/21 • 12:19