nach/acc.to/selon DIN EN 10204 - 2.2	**Data sheet**	ATB Technology in Motion

Motor type:	AF90L/2D-12		Description:	Three-phase A.C. Motor	
Motor no.:			Part no.:	588655	
Enclosure:	IP65		Mounting:	IMB34	
Drawing:	E242406_A005		Tested in acc. with:	DIN EN 60034	
Insulation class:	F		Ambient temperature:		
Rated output:	2,2	kW	Duty:	S3-60%	
Rated output 2 :	3,2	kW	Duty 2 :	S3-15%	
Rated output 3 :	2,6	kW	Duty 3 :	S3-60%	
Rated output 4 :	3,2	kW	Duty 4 :	S3-15%	
Rated voltage:	380-415/220-240	V	Rated current:	4,90/8,60	A
Rated voltage 2 :	380-415/220-240	V	Rated current 2 :	6,30/11,0	A
Rated voltage 3 :	460-480/265-280	V	Rated current 2 :	4,50/7,80	A
Rated voltage 4 :	460-480/265-280	V	Rated current 4 :	6,30/11,0	A
Connection:	Y / Δ				
Rated frequency:	50	Hz	Rated speed:	2850	rpm
Rated frequency 2 :	50	Hz	Rated speed 2 :	2805	rpm
Rated frequency 3 :	60	Hz	Rated speed 3 :	3440	rpm
Rated frequency 4 :	60	Hz	Rated speed 4 :	3400	rpm
Power factor:	0,90		Efficiency class:		
Power factor 2 :	0,93		Efficiency:	100%	Load
Power factor 3 :	0,91		Efficiency 1 :	81,5	%
Power factor 4 :	0,93		Efficiency 2 :	79,5	%
			Efficiency 3 :	82,0	%
			Efficiency 4 :	82,1	%
Brake type: Brake torque: Rated voltage:			Starting current:	7,2	fold
Declaration of EC-Conformity:	K001/09.11				
			Starting torque:	3,2	fold
Certificate of conformity:	- / -				
Temperature class / Temperature rise time (tE)			Pull-out torque:	3,3	fold

Comments

Spielberg, 12.05.2017

i.A. Wallner

gespeichert unter: 588655.xls