Industrial Steel Bottle Jacks

▼ Shown: **GBJ-010, GBJ-030, GBJ-003**



GBJ Series




Capacity:
2 - 100 ton

Stroke:
62 - 460 mm



Screw Extension Feature
Heat treated, adjustable extension screw with cleated saddle on selected GBJ models helps adjusting and prevents slipping.

- **Lower handle effort reduces operator fatigue**
- **Fully serviceable**
- **High-strength beam and pump linkage for long life**
- **Pumping handle included on all models**
- **Safety relief valve to prevent overload**
- **Automatic by-pass port to prevent over-extension**
- **Wiper seal for extended life**
- **Thick base material with large area for increased strength and stability during lifting.**



Cylinder-Pump Sets
As an alternative to bottle jacks where the operator is required to stand remote from the jacking point, see our range of cylinder-pump sets.

Page: 58

Jack Capacity ton (kN)	Stroke (mm)	Model Number	Screw Extension (mm)	Minimum Height (mm)	Maximum Height (mm)	Plunger diameter (mm)	Saddle Diameter (mm)	Bottom Plate Dimensions W x L (mm)	(kg)
2 (19,6)	460	**GBJ002L**	-	570	1030	29,0	-	127 x 127	6,0
2 (19,6)	100	**GBJ002**	50	160	310	21,0	21	95 x 111	3,6
3 (29,4)	105	**GBJ003**	65	168	338	24,0	24	95 x 116	3,9
5 (49,0)	150	**GBJ005**	75	212	437	29,0	29	95 x 123	5,0
8 (78,4)	150	**GBJ008**	75	219	444	33,0	37	95 x 138	5,9
10 (98,0)	150	**GBJ010**	75	219	444	37,0	37	95 x 142	6,5
10 (98,0)	62	**GBJ010S**	30	131	223	37,0	37	95 x 142	5,5
15 (147,0)	150	**GBJ015**	75	228	453	44,5	44	112 x 163	9,0
20 (196,0)	150	**GBJ020**	75	234	459	51,0	58	127 x 171	12,1
20 (196,0)	105	**GBJ020S**	55	190	350	51,0	58	127 x 171	10,0
30 (294,0)	150	**GBJ030**	75	242	467	57,5	65	142 x 196	15,5
50 (490,0)	150	**GBJ050**	-	252	402	80,0	80	180 x 230	28,5
100 (980,0)	150	**GBJ100**	-	300	450	110,0	94	296 x 333	87,0

All GBJ Jacks meet or exceed: ANSI, PALD, CE.