



**officine
orobiche**

Quantity

6

Offer No.

P20-4328 Pos. 1 of 1 Rev. 0

Model

CVM20.JL.MO.M4.WP.XX

Tag

s1
s2
s3
s4
s5

s6
s7
s8
s9
s10

s11
s12
s13
s14
s15

s16
s17
s18
s19
s20

01 Body mat. SS 316L
02 Connections 3/4" ANSI 150 RF 125-250 AARH
03 Float MONEL
04 Magnetic sleeve Nickel
05 Flow indicator YES

21 Body rating
22 Max press. 10 barg
23 Max temp. 100 °C
24
25 Fluid H2O

06 Housing ALUMINIUM WP IP 66
07
08 Area Classification .

09 Electric connection 1/2 " NPTF
10 Switch groups 1
11 Microswitch M4
12 Contact SPDT (125 V DC 0,5 A)

26 Nominal flow 2 m3/h
27 Range 0.4---1 m3/h
28 Set (min) 0,6 m3/h
29 Differential 0,6 m3/h
30 Normal flow 2 m3/h
31 Adjust.(min) on site
32 Scale CM 29 (mc/h)

13 Connector
14 Cable gland
15 Fins
16 Label ALUMINIUM
17 Paint stc 088 (silic.)


33
34
35
36
37 Nace NO

18 Well pipe MONEL
19 Internal parts MONEL
20 Antisteam


38 Cone mat. MONEL
39
40

v1
v2
v3
v4
v5

n1 AS OUR F.90930.2
n2 (but with float in monel)
n3
n4



X



nov-20

Issued UV.....date

Approved UT.....date