



officine
orobiche

quantity

1

off No.

P18/3257 pos 1 of 2 rev 0

model

CV50.A.2.M2.WP

tag

s1
s2
s3
s4
s5

s6
s7
s8
s9
s10

s11
s12
s13
s14
s15

s16
s17
s18
s19
s20

01
02
03
04
05

body mat.
connections
float
attraction sleeve
flow indicator

CARBON STEEL
2" ANSI 150 RF 125-250 AARH
AISI 316
AISI 430
NO

21
22
23
24
25

body rating
max-press.
max-temp.
fluid

10 barg
100 °C
H2O

06
07
08

housing ALUMINIUM WP IP 66
AREA .

26
27
28

nominal flow
range
set (min)

10 m3/h
2---5 m3/h
2 m3/h

09
10
11
12

electric connection
switch groups
microswitch
contact

1/2 " NPTF
1
M2
SPDT (220 V AC 10 A)

29
30
31
32

diff.
normal flow
adjust.(min)
scale

3 m3/h
10 m3/h
on site
.

13
14
15
16
17

connector
cable gland
fins
label
paint

ALUMINIUM

33
34
35
36
37

nace

NO

18
19
20

tube
internal parts
antisteam

AISI 316
AISI 316

38
39
40

mat_cone



BRASS

v1
v2
v3
v4
v5

n1
n2
n3
n4

X

.



gen-18

issued UV.....date