

ELECTRONIC DOSING PUMP LMI SERIES B1 / C1



Main technical Specifications

- Mechanically actuated diaphragm electromagnetic pump
- Maximum temperature of pumped chemical: 50 °C
- Self priming height: 1.5 m
- Accuracy: $\pm 2\%$ of adjusted output

B1 Series

- Maximum output: 26 l/h
- Maximum pressure: 10.3 bar
- Adjustable frequency: 1 to 100 spm
- Adjustable stroke length: 0 to 100%
Recommended minimum: 10%

C1 Series

- Maximum output: 76 l/h
- Maximum pressure: 20.7 bar
- Adjustable frequency: 1 to 100 spm
- Adjustable stroke length: 0 to 100%
Recommended minimum: 10%

Wide Variety of Applications

- Pump head and valves in PVC, PVDF, Acrylic or 316L S.S. plus designs for high viscosity polymer.
- Ceramic balls and Aflas or PTFE seats.
- Composite pump diaphragms of the superior Fluorofilm® assure reliable and leak free operation in a wide variety of chemicals.

Unique Features

- Uses LMI's unique molded long life Electromagnetic Power Unit (EPU) with electromagnetically balanced construction.
- Clog resistant injection check valves with flexible flapper nozzle are standard.
- LMI's unique 4-Function Valve or multifunction Auto-Bleed Valve are low cost options.

Simple Rugged Construction


- Thick wall glass fiber or carbon fiber reinforced thermoplastic construction plus integrated metal-plastic structural and magnetic components result in vibration and shock resistance not ordinarily found in competitive products.
- Strong automotive type wire and electrical connectors add to its construction strength.

Totally Enclosed Corrosion Resistant IP65

- O-Ring sealed corrosion resistant enclosure of glass fiber reinforced polypropylene protects the pump from harsh chemicals and tough environments.

Complete with Accessories

- LMI B1 / C1 dosing pumps come complete with:
 1. injection check valve,
 2. foot valve,
 3. ceramic weight.
- Most models are also available with factory tubing.



Specifications

Model	OUTPUT (l/h) max.	PRESSURE (bar) max.	LIQUIFRAM size (Inch ²)	STROKE CAPACITY (ml)		FREQUENCY (spm)		LIQUID END BODY/SEATS MATERIAL						TUBING CONNECTIONS	
				min.	max.	min.	max.	PVC/Aflas	PVDF/Aflas	PVDF/PTFE	Acrylic/Aflas	316L/PTFE ⁽¹⁾	High Visc. ⁽²⁾	Inch	Metric
B11*	6.0	10.3	0.9	0.10	1.00	1	100	398XY	392XY	393XY	390XY	297	85HV	.375"OD	6x8 mm
B12*	9.5	6.9	0.9	0.16	1.58	1	100	398XY	392XY	393XY	390XY	297	85HV	.375"OD	6x8 mm
B13*	17	3.4	1.8	0.28	2.83	1	100	368XY	362XY	363XY	360XY	277	75HV	.375"OD	6x8 mm
B14*	26	2.0	3.0	0.44	4.42	1	100	318XY	312XY	313XY	310XY	27	25HV	.500"OD	9x12 mm
C10*	4.9	20.7	0.9	0.08	0.81	1	100	94S ⁽³⁾	—	—	—	297	—	1/4"NPTm	—
C11*	9.5	10.3	1.8	0.16	1.58	1	100	368XY	362XY	363XY	360XY	277	75HV	.375"OD	6x8 mm
C12*	15	6.9	1.8	0.25	2.52	1	100	368XY	362XY	363XY	360XY	277	75HV	.375"OD	6x8 mm
C13*	30.4	4.1	3.0	0.51	5.05	1	100	318XY	312XY	313XY	310XY	27	25HV	.500"OD	9x12 mm
C14*	76	1.7	6.0	1.26	12.60	1	100	35T/M ⁽⁴⁾	—	32/M	30/M ⁽³⁾	37	—	.500"OD	9x12 mm

* When ordering, specify the voltage code by using one of the following numbers:

- 1 = 115 V, US Plug
- 3 = 230 V, CEE Plug
- 5 = 230 V, UK Plug
- 7 = 230 V, CH Plug
- 8 = 115 V, without Plug

⁽¹⁾ 1/4" NPTm connection for 277 and 297 - 1/2" NPTm for 27 and 37



⁽²⁾ .500" OD / 15x23

⁽³⁾ Seats in PTFE

⁽⁴⁾ PP/PTFE

X	Y	Refer to liquid end chart for complete option code
	0	Pipe thread 1/2" BSP
	2	Inch tubing
	3	Metric tubing
	4	Reinforced PVC tubing 6x12
B		Bleed 4 function valve included
N		No function valve
S		4 function valve included
T		3 function valve included

Dimensions



	W	X	Y	Z
Pump without function valve	82.5	216	16.5	272
Pump with function valve	115.5	259	16.5	305
Pump with large head (C14)	107	244	0	295
High viscosity pump	90	241	16.5	279
Packing:	B = 325 x 235 x 290 mm C = 380 x 235 x 290 mm			Gross Weight: B = 6.9 kg C = 8.7 kg



FRANCE - DOSAPRO MILTON ROY S.A.
10, Grande Rue - 27360 Pont Saint Pierre
Tel. : +33 (0)2 32 68 30 00 - Fax : +33 (0)2 32 68 30 93
www.dosapro.com - email : contact@dosapro.com

ESPAÑA - DOSAPRO MILTON ROY IBERICA
C/Embajadores, 100 - 28012 MADRID
Tel. : +34 91 517 80 00 - Fax : +34 91 517 52 38
www.dosapro.es - email : dmri@dosapro.es

UNITED STATES - LIQUID METRONICS, INC
201, Ivyland Road - Ivyland, PA 18974 USA
Tel. : 1 (215) 293 0401 - Fax : 1 (800) 327 7563
www.lmipumps.com

INTERNATIONAL SALES and PROJECTS DEPARTMENT
10, Grande Rue - 27360 Pont Saint Pierre (France)
Tel. : +33 (0)2 32 68 30 12 - Fax : +33 (0)2 32 68 30 91

SPARE PARTS DEPARTMENT/PIÈCES DE RECHANGE
10, Grande Rue - 27360 Pont Saint Pierre (France)
Tel. : +33 (0)2 32 68 30 01 - Fax : +33 (0)2 32 68 30 92
email : spare.parts@dosapro.com

INTERNATIONAL TECHNICAL ASSISTANCE/ASSISTANCE TECHNIQUE
10, Grande Rue - 27360 Pont-Saint-Pierre (France)
Tel. : +33 (0)2 32 68 30 02 - Fax : +33 (0)2 32 68 30 96
email : support@dosapro.com

DOSAPRO MILTON ROY EN FRANCE :
Angers, Bordeaux, Lille, Lyon, Nancy, Paris, Rouen