



 Officine Orobiche		data sheet for level switch series 40					doc. N. P19/160	
		quantity 2			pos 1 of 2 rev 0			
		model 41A.PF.PF.2M6.WP.XX						
tag		fluid	Density kg/dm3	temp. °C min/oper/des	press. barg min/oper/des	switch point mm H/L H/L		
s1		LIQUID	0,9	/20./20	6./6			
s2								
s3								
s4								
s5								
s6								
s7								
s8								
s9								
s10								
01	connections pos.	TOP						
02	connections type	4"ANSI 150 FF .						
03	.	.						
04	body mat.	PVDF	26	label body rating hydraulic test (bar) . . form dim. drawing		ALUMINIUM PN6 9 . . FIG.1 A-313		
05	attraction sleev	AISI 430	27					
06	Nipple/Enclus. Tube	AISI 316	28					
07	antisteam	NO	29					
08	internal parts	AISI 316	30					
09	spring	AISI 316	31					
10	rope	HASTELLOY C L=5m	32					
11	.	.	33					
12	float	PVDF	34					
13	.	n°1 Ø90X200mm	35					
14	.	.	36					
15	nace	no	37					
16	paint	.	38					
17	.	.	39					
18	housing	ALUMINIUM WP IP 66						
19	finis	.						
20	switch groups	n°1 M6 (GOLD PLATED) DPDT (28VDC 0,01 A) RES .						
21	electric connection	1/2" NPTF /// .						
22	amb. Temp. min/max	0 / 45°C		 Fig. 1  Fig. 2  Fig. 3				
23	PED 2014/68/UE	Art. 4.3						
24	AREA	.						
25								
v1								
v2								
v3								
v4								
v5								
n1	as our F.62050							
n2								
n3								
n4								
n5								
issued UV.....date								dic-18