macnaught
POSITIVE DISPLACEMENT METERS

Model: MX40P-1TE



1 1/2" Oval gear flow meter designed for a broad range of Industrial Process applications.

- Stainless Steel construction
- FEP - Teflon® encapsulated seals
- Max flow rate 250 LPM / 66 GPM
- Temperatures up to 150°C
- Accuracy +/- 0.5% (0.25% available)
- Available with BSP(Rp), NPT, DIN, JIS or ANSI process connections
- Suitable for high viscosity fluids

Select a Flowmeter

Step 1.Size

40 (1 1/2")

Step 2.Family

P series -INDUSTRIAL

Step 3.Process Connection

1 - BSP (Rp)

Step 4.Rotor Type

T - High Temp

Step 5.Pulser

E - 12mm LC Display (with outputs)

Process Connection

Port Size	1½"
Connection Type	BSP (Rp)

Material of Construction

Body	316SS
Rotor	316SS
Bushing	Carbon
Seal	FEP (Teflon®)

Technical Specifications

Flow Range	**<5cps**	**>5cps**
	15 - 235 LPM	10 - 250 LPM
	4 - 62 GPM	2.6 - 66 GPM
Max Pressure	10342 kPa	1500 psi
Temperature	-20 - 60°C	-4 - 140°F
K-Factor	Refer to Flowmeter Data Plate	
Accuracy	+/- 0.5% (0.25% available with reduced range)	
Repeatability	+/- 0.03%	

Service Kits

	Part Number	Description
Rotor Kit	MXS-40P-HTrotor	Rotor set and O-ring
Seal Kit	MXS-40P-seal	Meter Cap O-Ring - FEP (Teflon®)

Accessories

SS Y Strainer	YS040-01
Air Eliminator/Strainer	N/A
Wall Mount Adaptor	-
3 point cal check	MXA-3ptcal
Pressure test	MXA- PRESSTEST

macnaught
POSITIVE DISPLACEMENT METERS

Digital Display MX40P-1TE

macnaught
POSITIVE DISPLACEMENT METERS

DIGITAL DISPLAY TYPE: E



Type PRA 12mm LC Display (c/w outputs)

The PRA series is a meter mounted digital register with a 12mm LCD display, providing real-time indication of Flow rate, total and accumulated total. The output facilities include a 4-20mA, scaled pulse output and a High/Low flow alarm function.

Construction

Material	Polypropylene	
IP Rating	67	
Mounting	Meter Mount	
Connection	M-Lock ™	
Cable Entry	2x 12mm (blind)	
Dimensions	**Height (mm)**	**Diameter (mm)**
	48 mm	99 mm

Technical Specifications

Power Supply	**Battery**	**External Pwr Supply**
	3V Lithium	18-30VDC
Backup	EEPROM Flash memory	
Outputs	4-20mA	
	Scaled Pulse	
	Hi/Lo Flow	

Service Kits


Part Number	Description
MXS-PCB-PR	PCB + Housing to suit display types D, E
MXS-DIS-PRA	LCD unit to suit Disply PRA

LC Display

Digital Size	**Upper LCD**	**Lower LCD**	
	7 digit / 12mm	7 digit / 7mm	
Display	**Total**	**Acc Total**	**Flow Rate**
	resettable	non-resettable	User defined units

Dimensions MX40P-1TE

macnaught
POSITIVE DISPLACEMENT METERS



	METER AND FLANGE DIMENSIONS						PULSAR AND DISPLAY HEIGHT - F					
METER SIZE	**PORT SIZE**	**A**	**B**	**C**	**D**	**E**	**TYPE A**	**TYPE B, N**	**TYPE C**	**TYPE T**	**TYPE D,E**	**TYPE F,G,H**
MX06	1/4"	71	74	N/A	42	25	59	93	100	104	90	143
MX09	1/4"	71	74	N/A	42	24	59	93	100	104	90	143
MX12	1/2"	81	87	N/A	49	28	66	100	107	111	97	150
MX19	3/4"	100	112	N/A	62	37	79	113	120	124	110	163
MX25	1"	100	112	240	75	45	92	126	133	137	123	176
MX40	1 1/2"	120	137	240	103	61	120	154	161	165	151	204
MX50	2"	140	163	264	124	72	141	175	182	186	172	225