Pro-face

The easy way to Interface




## AGP3300-T1-D24-FN1M

| | |
|---|---|
| Display Size (diagonal + wxh in mm) | 5.7 inch (115.2 x 86.4) |
| Display Type | TFT colour LCD |
| Display Colours | 65536 colours |
| Display Resolution | 320x240 pixels |
| Backlight | CCFL service life 50000 hrs. at 25°C |
| | |
| Touch Panel Type | Resistive Film (analog) |
| Touch Panel Resolution | 1024x1024 |
| | |
| Application Memory | 6 MB FEPROM |
| Data Backup Memory | 320 KB SRAM |
| | |
| Serial Interfaces | 2 |
| Com 1 | RS232/RS422/RS485 |
| Com 2 | RS422/RS485 |
| Number of drivers that can be used simultaneously | 2 maxi |
| | |
| PLC Control Functionality | Yes |
| | |
| CF-Card I/F | Yes |
| Ethernet I/F | Yes |
| USB I/F | Yes |
| Video input | No |
| | |
| Voltage | DC 24V |
| Ratings | IP65 |
| Operating Temperature | 0°C to 50°C |
| Housing | Aluminium |
| External Dimensions (wxhxd in mm) | 167.5 X 135.0 x 59.5 |
| Cut-out Dimensions (wxh in mm) | 156.0 X 123.5 |
| | |
| DIO | No |
| CANopen Network | No |
| Flex Network | 512 bit I/O |
| | 128 integral I/O |
| | |
| Programming software | GP-Pro EX |

- 
- Colour TFT - 320 x 240
- 65536 colours
- CF card - Flex network
- DC 24V

