HEAT-SHRINKABLE TRIFURCATIONS KITS FOR MV APPLICATIONS
Up to Umax 19/33 (36) kV

Application
Designed to accommodate various single or three core cable terminations.

Technical description
The TK/1 kit consists of an anti-tracking breakout for the cable crotch area, 3pcs of GT2 anti-tracking tubes cover the cores.
The TK kit has the same components like TK/1 but has additional earth kit included for the armor.



TK/1
Unarmored cables





TK
Armored cables

Type tested acc.:
Cenelec HD 629.1 S2
IEC 60502-4

voltage Um kV	type	application range (mm^2)
12/17	TK1 - TK1/1	25÷185
	TK2 - TK2/1	95÷185
	TK3 - TK3/1	120÷300
	TK4 - TK4/1	185÷400
24	TK1 - TK1/1	25÷120
	TK2 - TK2/1	70÷185
	TK3 - TK3/1	150÷300
	TK4 - TK4/1	185÷400
36	TK1 - TK1/1	50
	TK2 - TK2/1	50÷120
	TK3 - TK3/1	120÷240
	TK4 - TK4/1	150÷400



Various tail length exist, please check requirements of your end customer and inform our sales office accordingly.



Contact our sales office for selecting exact breakout type.



For other cable types please contact our sales office.



Various earth connection design solutions exist for armoring. For exact details contact our sales office.



Various earth connection kits are available for screen connection. For exact details contact our sales office.