

Lifting Point Pewag PLE/N Eta



Weldable lifting point. High-tensile eyebolts pewag profilift eta, for welding onto machine parts or vehicle bodies. Ideal for hanging of lifting and lashing parts. Due to the integrated spring, the ring will be kept in each requested position.

The instructions according to DIN EN ISO 14341 are valid for the welding. The welding may only be carried out by a welding operator with a valid qualification according to EN 287-1. The lifting points will be packed individually and together with a user manual and welding instructions.

Permissible usage

Load capacity acc. to the inspection certificate respectively table of WLL in the mentioned directions of pull (see picture 1 and 2).

Non permissible usage

Make sure when choosing the assembly that improper load can not arise e.g. if:

- The direction of pull is obstructed
- Direction of pull is not in the foreseen area
- Loading ring rests against edges and load

Material: Alloy steel grade 8.

Marking: According to standard, WLL and the load capacity is clearly marked on the welding pad.

Standard: EN 1677-1

Safety factor: 4:1

Grade: 8






Select a row from the table below, then click the add to quote button

Part Code	Code	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	h mm	i mm	Weight kg
11.4292458	PLE/N 6	1.12	36	40	62	11	67	42	26	35	0.31
11.4295459	PLE/N 8	2	37	42	69	13	73	45	28	37	0.4
11.4295460	PLE/N 10	3.15	41	45	78	16,5	80	47	34	40	0.63
11.4295461	PLE/N 13	5.3	61	55	99	22	97	53	44	50	1.46
11.4295462	PLE/N 16	8	63	70	120	25	120	73	48	64	2.3
11.4295463	PLE/N 22	15	89	97	163	33	163	92	70	90	5.4

1

Add to quote

Method of lifting											
Number of legs		1	1	2	2	2	2	3+4	3+4	2	3+4
Angle of inclination		0°	90°	0°	90°	0°-45°	45°-60°	0°-45°	45°-60°	asymm.	asymm.
Code	Load capacity	Load capacity									
	tons	tons									
PLE/N 6	1,12	1,12	1,12	2,24	2,24	1,5	1,12	2,3	1,6	1,12	1,12
PLE/N 8	2	2	2	4	4	2,8	2	4,2	3	2	2
PLE/N 10	3,15	3,15	3,15	6,3	6,3	4,4	3,15	6,6	4,7	3,15	3,15
PLE/N 13	5,3	5,3	5,3	10,6	10,6	7,4	5,3	11,2	7,9	5,3	5,3
PLE/N 16	8	8	8	16	16	11,3	8	16,9	12	8	8
PLE/N 22	15	15	15	30	30	21	15	31,8	22,5	15	15

