



**officine
orobiche**

Quantity

2

Offer No.

P21-123 Pos. 1 of 2 Rev. 0

Model

CV15.A.2.M2.WP

Tag

s1
s2
s3
s4
s5

s6
s7
s8
s9
s10

s11
s12
s13
s14
s15

s16
s17
s18
s19
s20

01 Body mat. CARBON STEEL
02 Connections 1/2" GASF
03 Float SS 316
04 Magnetic sleeve SS 430
05 Flow indicator NO

21 Body rating
22 Max press. 9 barg
23 Max temp. 80 °C
24
25 Fluid H2O

06 Housing ALUMINIUM WP IP 66
07
08 Area Classification .

26 Nominal flow 1 m3/h
27 Range 0.2---0.5 m3/h
28 Set (min) 0,2 m3/h
29 Differential 0,3 m3/h
30 Normal flow 1 m3/h
31 Adjust.(min) on site
32 Scale .

09 Electric connection 1/2 " NPTF
10 Switch groups 1
11 Microswitch M2
12 Contact SPDT (24 V DC 1 A)

13 Connector
14 Cable gland
15 Fins
16 Label SS 316
17 Paint stc 088 (silic.)



33
34
35
36
37 Nace NO

18 Well pipe SS 316
19 Internal parts SS 316
20 Antisteam

38 Cone mat. SS 316
39
40

v1
v2
v3
v4
v5
n1
n2
n3
n4

X



nov-20

Issued UV.....date