

POP® PB2500

Battery-operated rivet tool for installing 3.0 mm to 4.8 mm blind rivets

Benefits at a glance

- Cordless tool for maximum mobility, prevents injury
- Exceptionally high installation speed
- Brushless DC motor (BLDC)
- Up to 900 installations / battery charge (test performed using St/St 4.8 mm blind rivets and 1.5 Ah battery)
- Super-fast charging of 2.0 Ah battery in 30 minutes
- 25 mm stroke at 8.5 kN for numerous applications
- Powerful 18V lithium-ion battery for superior performance (DeWalt compatible)
- Battery status indicator
- No memory effect
- Lightweight: just 1.7 kg incl. 2.0 Ah battery

Technical specifications

Stroke:	25.0 mm
Insertion force:	8.5 kN
Motor:	18.0 Volt brushless DC motor
Length:	320 mm
Height:	240 mm
Nose cap ø:	20.6 mm
Nose cap length:	47.0 mm
Weight:	1.7 kg with battery (2.0 Ah)

Scope of delivery

POP PB2500 battery-operated rivet installation tool
 18.0 V charger
 18.0 V / 2.0 Ah insertable battery
 Nose pieces: 3.0 / 3.2 mm; 4.0 mm; 4.8 / 5.0 mm
 Storage case
 Operating instructions
Article No. 329 500 002

Working range

Rivet Ø [mm]	2.4	3.0/3.2*	4.0	4.8/5.0	6.0	6.4
Aluminium, copper, brass		•	•	•		
Steel		•	•	•		
Stainless steel		•	•	•		

* Not suitable for cup-type blind rivets.

Batteries and chargers

Description	Article No.
18V 2.0 Ah PB2500/3400 battery pack	329 500 963
18V 3.0 Ah PB2500/3400 battery pack	329 500 964
PB2500/3400 charger	329 500 959



Spare parts / Consumables

Description	Article No.
Rivet-holding nose piece 4 (3.2 mm – 1/8")	329 500 102
Rivet-holding nose piece 5 (4.0 mm – 5/32")	329 500 103
Rivet-holding nose piece 6 (4.8 mm – 1/16")	329 500 101
Jaw slider 4 (3.2 mm – 1/8")	329 500 112
Jaw slider 5 (4.0 mm – 5/32")	329 500 113
Jaw slider 6 (4.8 mm – 1/16")	329 500 111
Jaw case	329 500 109
Jaws, 3-piece	329 500 108
Jaw spring	329 500 114
Slide bearing for container lid	329 500 136
Container lid	329 500 139
Nose cap	329 500 909

Optional accessories

Description	Article No.
Fixing kit for balancer	329 500 972

"Pro" rivet-holding nose pieces

Description	Article No.
Rivet-holding nose piece 4 (3.2 mm)	329 500 980
Rivet-holding nose piece 5 (4.0 mm)	329 500 981
Rivet-holding nose piece 6 (4.8 mm)	329 500 982

Fitted with a safety mechanism for longer tool life.

Special fittings for installing special rivets

Description	Article No.
Jaws recommended for 3.2 and 4.0 stainless steel rivets	329 500 970
Jaw slider for stainless steel rivets	329 500 971