

Heat Detector Tester
Salwico SOLO 461

Part no. N1743

System: All Salwico fire alarms

Description

The Salwico SOLO 461 is a cordless heat detector tester for the Salwico heat detectors. The tester suits point type, rate of rise, fixed temperature and combination detectors up to 90°C.

Under the control of a microprocessor, blown air is heated by the element just before exiting the duct. This minimise the possibility of heat damage the plastic of the detector.

The tester is activated when an infra-red beam is broken by the detector.

For battery charging instruction and general information, see the manual delivered in the box.

Data

Numbers of test	Typical 50 tests of 30 sec
Battery charger	110-240 VAC 12 VDC (lighter socket)
Standby	120 sec
Auto power off	5 min
Operating temperature	+5°C to +45°C
Storage temperature	-10°C to +50°C
Ambient humidity	0 to 85% RH
Dimension	Inside diameter 100 mm
Material	Plastic
Colour	Black / Red
Weight	~600 g

Test kit



Cordless heat detector test kit including:
1x Cordless heat detector tester
2x Batteries
1x Universal battery charger

Cautions:

- Only for use in safe areas.
- Store in clean, dry space.
- Keep away from children
- The tester may be hot after use.
- Do not use tester in wet conditions.

Consilium
Consilium Marine AB
P.O. Box 8763, SE-402 76 Göteborg
Phone +46 31 7107700 Fax +46 31 7107800
www.consilium.se