



ART. 92C/701

Industrial pumps - s. 900

Integral pump s. 900, for grease or oil with high viscosity, with PU seals and suction tube in steel for drums 50 ÷ 60 kg



FLUIDS

FRESH OIL | GREASE

SECTORS

AERONAUTIC | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

Features	UM	Value
Flow rate	l/min	3000 g/min
Ratio		70:1
Compatible fluids		high viscosity oils and greases
Suction tube upper body		carbon steel
Suction tube		carbon steel
Air inlet connection		G 1/2" (f)
Fluid outlet connection		G 1/2" (f)
Max supply pressure	bar	8
Max air consumption 8 bar	m ³ /min	1,6
Noise level	dB	80
Suitable for drums or tank		suitable for drums 50 ÷ 60 kg
Packing	N° - m ³	1 - 0,070
Weight	kg	18
Dimensions (A-B-C)	cm	43 - 74 - 4,5

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.