

Data sheet

LANDEFELD

Elbow push in fitting G 1/8"-6mm, IQS standard

Item number:

IQSL 186 G ♡



Example illustration

Item description

Materials:

Body: nickel-plated brass / PA 66, sleeve: PA 66 (M 3: nickel-plated steel / PA66), seal: NBR, holding claws: stainless steel, cartridge: Zinc-plated ZnDC (only silicone-free seals and lubricants are used during assembly)

Temperature range:

-20°C to +80°C

Operating pressure:

-0,95 to 20 bar

Media:

oiled and unoled compressed air, neutral gases and water (water up to max 60° C may be used only after we have approved the performance specifications).

Advantages:

- Wide variety of products,
- extremely tight due to lip seal,
- available with conical, PTFE-coated thread or with cylindrical thread and captive O-ring

Properties

G	G 1/8"
D [mm]	6

Further information:

Weight	8,2 g / pcs
GTIN	4050571378929
Customs duty number	74122000

RoHS compliant	Yes
Manufacturer	Sang-A

More information on this item and the process for ordering it can be found in our online shop
<https://www.landefeld.de> under item number **IQSL 186 G**.

Landefeld Druckluft und Hydraulik GmbH · Konrad-Zuse-Straße 1 · 34123 Kassel · Germany

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.

As of: 13.10.2023