

ROTEX AUTOMATION EUROPE

Address : Bierstraat 117, 3011 XA Rotterdam, The Netherlands

Website : www.rotexautomation.comE-mail : europe@rotexautomation.com*Engineering For The Future***DATASHEET**

Type of Valve	: 3/2 Direct acting Universal Valve
Ordering Code	: 30308-5-2G+III-110V-AC/DC-16-FR-H-CE
Item Code	: 93000001575
Port Connection	: 1/4" BSP(F)
Orifice Size (mm)	: 5 mm
Flow Factor (kv)	: 8 LPM
Body Material	: Aluminium Hard Anodised
Manual Override	: Manual Override Not Provided
Seat Seal Material	: NBR
Media	: Air
Main Pressure	: 0 - 10 bar
Media Temp Range	: -25°C to +75°C
Type of Solenoid	: Weather Proof Enclosure having integral Terminals, Horizontal Cable Entry 1/2"NPT(F), IP67
Size of Coil	: III
Enclosure Material	: Aluminium Cast Epoxy Powder coated
Special Version	: Inbuilt Full Rectifier with Surge Suppressor
Voltage	: 110V 50Hz/ 60Hz/ DC, 120V 50Hz/ 60Hz/ DC (-20%, +20%)
Power of Coil	: 8 W
Insulation Class	: Class H
Approval	: CE
Coil Certificate nr.	: D/QA/07
Marking	: Weather Proof IP67

Created By: Sumit Rawat **Print Date And Time:** 15/03/2024 01:17

This is System Generated Report

Rotex Automation Europe is a registered trademark of Rotex Controls B.V.

Rotex Controls B.V. - VAT nr. NL819933259B01

Trade reg : 24443687 Rotterdam

Bankers : ABN Amro : 59.69.83.441 - IBAN : NL34ABNA0596983441 - BIC : ABN ANL 2A.

Phone : + 31 88 505 3 505