


Data Sheet

Itemnumber..... 3242252209



AC = 463	DB = M20	EG = 56	GD = 11	L = 897	M = 400	S = 8-Ø18.5	TL = 192
AD = 347	E = 140	F = 18	H = 225	LA = 20	N = 350	T = 5	
D = 60	EB = 110	G = 53	HB = 307	LB = 754	P = 450	TB = 260	

Version

Type..... HMC2 225M1-4
Design..... Induction motor
Standard series..... IEC 60034
Phase / Voltage range..... 3~ / Low

Electrical design

Efficiency..... IE2
Pole..... 4
Power at 50 Hz (kW)..... 55,0
Hz..... 60 (60 Hz output)
Voltage..... 440VD 60 Hz
Winding voltage..... 400VD/690VY 50 Hz
Power output (kW)..... 64,0
Duty..... S1
Insulation class..... F
Temperature rise..... B

Mechanical design

Frame size..... 225M1
Mounting..... B5
Rain cap..... No
Protection class..... IP55
Cooling method..... IC411/TEFC
External grounding..... Yes
Drain hole..... Yes
Frame material..... Cast Iron
Material approval..... None
Shaft..... IEC Standard
Key..... Closed key
Balancing..... Half key balancing
Vibration class..... Grade-A
Weight (kg)..... 425

Environment condition

Ambient temp. min. (°C).... -20
Ambient temp. max. (°C).... 45
Altitude (mtr up to)..... 1000

Bearing

DE Bearing..... 6314-ZZ/C3
NDE Bearing..... 6313-ZZ/C3
Fixed bearing..... DE

Terminal box

Tbox position..... Top
Cable entry direction..... Right (from DE)
Cable entry
Main..... 2 x M50x1,5
Ø32-38mm metal
Accessory..... 2 x M20x1,5
Metal blindcaps
Connection type..... Delta (D)
Terminal board thread..... 6-M8

Test values

Rotor inertia (kgm²)..... 0,90
No load current (A)..... 39,0
Winding resist. (ohm)..... 0,099
Starting time (sec.)..... 0,17

Motor protection

Thermal protection main..... PTC 3x 155 dgr
Thermal protection second.. None
Space heater..... 1x 230V
Temperature detector..... No
SPM..... No
IR wire..... No
Tropical insulation..... Yes

Explosion protection

According to..... None

General

Direction of rotation..... CW
Painting..... RAL 9005 Gloss 10
Nameplate..... Multivoltage + VFD
Special packing..... No
Special requirements..... No

Rated power (kW)	55,0	53,5	66,0	64,0
Frequency (Hz)	50	50	60	60
Voltage (V)	400 690	380 660	480 830	440
Connection	D Y	D Y	D Y	D
Full load current (A)	100 58,0	104 59,5	100 58,0	104
Speed (rpm)	1490	1490	1780	1780
Power factor cos(phi)	0,85	0,86	0,85	0,87
Efficiency, 100/75/50 (%)	93,9/94,0/93,5	93,9/94,0/93,5	93,9/94,0/93,5	93,5/93,6/93,1
Ist/In	6,9	6,1	6,9	6,4
Full load torque (Nm)	355	345	355	345
Tst/Tn	2,3	2,1	2,3	2,0
Tmax /Tn	3,3	3	3,3	2,8
Duty	S1	S1	S1	S1
Ambient temp. (°C)	40	45	40	45