



The Air-operated Grease Pump with pressure ratio from 25:1 is suited especially for delivering lubricants, as decanting and filling systems or for the filling of gearboxes or in centralised lubricating systems.

ABNOX Air-operated Grease Pump from type S is suitable for transferring of lubricants of medium to high viscosity levels as well as silicon greases and silicon oils.

This Air-operated Grease Pump is renowned for their high efficiency as well as their extremely low noise levels. Outstanding reliability due to high quality materials, seals and special change-over valve.

Recommendation from ABNOX:

Never let the pump system and especially not the suction tube rest on the floor. Keep them away from dirt, you will avoid damage to the pump and expensive repairs.

This Air-operated Grease Pump from type S is qualified for delivering silicon greases and silicon oils with a viscosity up to 60'000 cST.

Not suitable for hardening and abrasive media, or with abrasive filling substances!.

4062200- Air-Operated Grease Pumps, Model: 25:1/Type S, Container height:470mm, Version: Container 20-25kg

Capacity container (kg)	20-25kg
Container height (mm)	470
Suction tube dia. (mm)	32
Suction tube length (mm)	473
Min./Max temperature	10/40
Specification for operation medium	Lubricants up to NLGI 3/5'000'000 m Pa.s
Output pressure (medium) at operating pressure 6 bar [bar]	140
Output pressure (medium) at operating pressure 10 bar [bar]	233
Delivery rate pro double stroke (cm3)	17
Delivery rate at pump outlet (cm3/min)	1'295
Inlet operating pressure (compressed air) optimum [bar]	6
Max. air consumption [l/min]	217
Connection (compressed air) optimum [bar]	1/4" BSP
Connection (Medium) thread Thread P	1/4" BSP

SPARE PARTS	
Seal Kit Suction System	4061900
Seal Kit Air Motor	4879800

To reach a friendly voice, call during our hours of operation:
Monday through Friday, 9 a.m. to 6 p.m. EST
(Eastern Standard Tim)

Wood Tech Enterprises
Our website: www.woodtechtooling.com

P.O. Box 2226
Fairview, NC 28730 USA

1-800-TOOLING (866-5464)
Phone: 828-628-4414
Fax: 828-628-4490

Shipping Address:
15 Khristy Scott Lane
Fairview, NC 28730 USA

Copyright © 1998-2014 Wood Tech Enterprises, Inc. All Rights Reserved. Designated trademarks and brands are the

property of their respective owners. Wood Tech is not responsible for typographical errors. Prices are subject to change. All prices are in U.S. Dollars.