


Product Specifications

Part Number: VAG-3521-181D-XV9-D220**Description:** Versa V Series Directional Control Valve**Title:** Valve, 3-Way, Brass, 220VDC**Actuator(s):** Solenoid-Pilot \ Hand Lever-Latch on Spring Return**Function:** 3-way, 2-position, Normally Closed

Body:	Body Ported, 1/2" NPT
Pressure Range:	55-175 psi 3.79-12.1 bar
Flow:	4.0 Cv
Media:	Air - Inert Gas Natural Gas
Temperature Rating	-4°F to 189°F -20°C to 87°C

Maintenance & Documentation

Repair kit:	V-4532
Replacement operator:	E4-3198-33XV-HT-LX-D220
Operation & Installation:	
Catalog:	V & T Series Catalog



Materials of Construction

Body:	Brass
Seals, Valve Proper:	Buna
Weight:	7.06 lb 3.2 kg



Solenoid Specifications

Description:	Hazardous Location - E4 Class XV Option
Operating voltage:	220 V DC $\pm 10\%$
Power (nominal):	1.8 W
Inrush:	8 mA
Holding:	8 mA
Resistance:	26887 Ω
Solenoid Ingress Protection:	NEMA 4X & 6P IP66 / 67 / 68
Electrical Protection:	Not applicable
Coil class:	H
Duty cycle:	Continuous Duty
Protection:	CI I, Grps B,C,D - CI II, Grps E,F,G - CI III
Zone:	Zone 1
T rating (gas):	4
Certification:	cCSAus



Operator Construction

Solenoid housing material:	Stainless Steel - Plated
Solenoid seal material:	FKM
Coil:	Epoxy Molded
Solenoid Connection:	1/2" NPT female conduit with 24" wires