ROTEX AUTOMATION EUROPE
Address : Bierstraat 117, 3011 XA Rotterdam, The Netherlands
Website : www.rotexautomation.com
E-mail : europe@rotexautomation.com

ROTEX
Engineering For The Future

DATASHEET

Type of Valve	:	5/2 Internal Pilot Operated Single Solenoid Valve
Ordering Code	:	51400-6-2R-B5+III-230V-50HZ-16-H-CE
Item Code	:	93000000513
Port Connection	:	1/4" NPT(F)
Orifice Size (mm)	:	6 mm
Flow Factor (kv)	:	12 LPM
Body Material	:	Stainless Steel 316 with internal wetted parts of Stainless Steel 316
Manual Override	:	Manual Override Provided Push to operate momentarily, for stayput using Screw Driver push & turn CW to operate valve
Seat Seal Material	:	NBR
Media	:	Air
Main Pressure	:	2 - 10 bar
Media Temp Range	:	-25°C to +75°C
Type of Solenoid	:	Weather Proof Enclosure having integral Terminals, Horizontal Cable Entry 1/2"NPT(F), IP67
Size of Coil	:	III
Enclosure Material	:	Aluminium Cast Epoxy Powder coated
Voltage	:	230V 50Hz/ 240V 60Hz (+20%, -20%)
Power of Coil	:	6 W
Insulation Class	:	Class H
Approval	:	CE
Coil Certificate nr.	:	D/QA/07
Marking	:	Weather Proof IP67

Created By: Sumit Rawat Print Date And Time: 14/08/2024 20:47

This is System Generated Report

Rotex Automation Europe is a registered trademark of Rotex Controls B.V.
Rotex Controls B.V. - VAT nr. NL819933259B01 Trade reg : 24443687 Rotterdam
Bankers : ABN Amro : 59.69.83.441 - IBAN : NL34ABNA0596983441 - BIC : ABN ANL 2A.
Phone : + 31 88 505 3 505