

403AA01072A 

S217AN-2 SOLENOID VALVE, S217-A-N-2

Image coming soon

| PRODUCT DETAILS              |                               |
|------------------------------|-------------------------------|
| Gross weight                 | 0.093 Kilogram                |
| Net weight                   | 0.093 Kilogram                |
| Brand                        | Danfoss                       |
| Cavity                       | A879                          |
| Coil termination             | None                          |
| Diode                        | No                            |
| Flow rate lpm                | 10                            |
| Fluid compatibility          | MIL-H-5606, SAE10, SAE20, etc |
| Function                     | Solenoid Valve                |
| Housing                      | No                            |
| Installation type            | Screw-in Cartridge            |
| Model code                   | S217-A-N-2                    |
| Number of housing ports      | 2                             |
| Number of valve ports        | 2                             |
| Operating temperature        | -40 C to 120 C (-40 to 248 F) |
| Operation                    | Electrically operated         |
| Override type                | None                          |
| Port type                    | Cartridge Only                |
| Pressure rating BAR          | 210                           |
| Product group                | All Cartridge Valves          |
| Product Name Description     | On Off Solenoid               |
| Recommended filtration level | 18/16/13                      |
| Seal type                    | Nitrile                       |
| Special features             | None                          |
| Style                        | Bi-Directional 2-Way 2-Pos NC |
| Type                         | Cartridge Solenoid Valves     |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)