unidirectional pump - series XV

STANDARD EUROPEAN PUMP
ø25.4 FLANGE - TAPER SHAFT

XV-1P

X	1	P	25	02	F	I	I	A

Series	X	series XV
Group	1	group 1
Category	P	unidirectional pump
Displacement	25	3.8
Flange	02	Ø25.4 STANDARD EUROPEAN right rotation
Shaft	F	CO001 - Tapered 1:8 - ø10 - M7x1 - key thk.2.4
Body IN	I	inlet - Ø30 Ø12 M6
Body OUT	I	outlet - Ø30 Ø12 M6
Cover	A	standard



XP101

Technical data table

TYPE	Displacement	Max. Pressure	CODE	
	cm3/rev	P1 bar	P3 bar	Left rotation	Right rotation
XV-1P/0.9	0,91	240	280	X 1 P 16 01 F I I A	X 1 P 16 02 F I I A
XV-1P/1.2	1,17	250	290	X 1 P 17 01 F I I A	X 1 P 17 02 F I I A
XV-1P/1.7	1,56	250	290	X 1 P 18 01 F I I A	X 1 P 18 02 F I I A
XV-1P/2.2	2,08	250	290	X 1 P 20 01 F I I A	X 1 P 20 02 F I I A
XV-1P/2.6	2,60	250	300	X 1 P 21 01 F I I A	X 1 P 21 02 F I I A
XV-1P/3.2	3,12	250	300	X 1 P 23 01 F I I A	X 1 P 23 02 F I I A
XV-1P/3.8	3,64	250	300	X 1 P 25 01 F I I A	X 1 P 25 02 F I I A
XV-1P/4.3	4,16	250	300	X 1 P 27 01 F I I A	X 1 P 27 02 F I I A
XV-1P/4.9	4,94	250	300	X 1 P 29 01 F I I A	X 1 P 29 02 F I I A
XV-1P/5.9	5,85	250	300	X 1 P 31 01 F I I A	X 1 P 31 02 F I I A
XV-1P/6.5	6,50	250	300	X 1 P 32 01 F I I A	X 1 P 32 02 F I I A
XV-1P/7.8	7,54	220	260	X 1 P 34 01 F I I A	X 1 P 34 02 F I I A
XV-1P/9.8	9,88	190	230	X 1 P 36 01 F I I A	X 1 P 36 02 F I I A

P1) Max. working pressure - P3) Max. peak pressure

For heavy-duty applications, it is recommended to check the admissible torque of the shaft

Dimensions table

TYPE	Weight	A	B	C	D	E	F	D	E	F
	kg	mm	mm	mm	IN			OUT		
XV-1P/0.9	0,950	78,1	37,3	66,1	ø12	30	M6x1	ø12	30	M6x1
XV-1P/1.2	0,970	79,0	37,8	67,0	ø12	30	M6x1	ø12	30	M6x1
XV-1P/1.7	1,010	80,5	38,5	68,5	ø12	30	M6x1	ø12	30	M6x1
XV-1P/2.2	1,030	82,5	39,5	70,5	ø12	30	M6x1	ø12	30	M6x1
XV-1P/2.6	1,060	84,5	40,5	72,5	ø12	30	M6x1	ø12	30	M6x1
XV-1P/3.2	1,090	86,5	41,5	74,5	ø12	30	M6x1	ø12	30	M6x1
XV-1P/3.8	1,120	88,5	42,5	76,5	ø12	30	M6x1	ø12	30	M6x1
XV-1P/4.3	1,170	90,5	43,5	78,5	ø12	30	M6x1	ø12	30	M6x1
XV-1P/4.9	1,200	93,5	45,0	81,5	ø12	30	M6x1	ø12	30	M6x1
XV-1P/5.9	1,260	97,0	46,8	85,0	ø12	30	M6x1	ø12	30	M6x1
XV-1P/6.5	1,300	98,5	48,0	86,5	ø12	30	M6x1	ø12	30	M6x1
XV-1P/7.8	1,360	103,5	50,0	91,5	ø12	30	M6x1	ø12	30	M6x1
XV-1P/9.8	1,500	112,5	54,5	100,5	ø12	30	M6x1	ø12	30	M6x1



T.1 = 24.5÷29.4 [Nm] - screw tightening torque M8 T.3 = 11.5 [Nm] - torque wrench setting 11

T.2 = 43 [Nm] - admissible shaft torque (N.B. When choosing a shaft, always check the admissible torque).

Table of variations

ø25.4 FLANGE

ø25.4 FLANGE			
Left rotation		Right rotation	
	01		02
	03		04
	05		06
	07		08

Shaft			
	F		D
	J		L
	Q		R

Cover		
Left rotation	Right rotation	
		A
		B
		C
		D
 Internal drainage		N
 External drainage		O

Displacement	
TYPE	CODE
XV-1P/0.9	**16**
XV-1P/1.2	**17**
XV-1P/1.7	**18**
XV-1P/2.2	**20**
XV-1P/2.6	**21**
XV-1P/3.2	**23**
XV-1P/3.8	**25**
XV-1P/4.3	**27**
XV-1P/4.9	**29**
XV-1P/5.9	**31**
XV-1P/6.5	**32**
XV-1P/7.8	**34**
XV-1P/9.8	**36**

Standard bodies						
Displacement cm3/rev	Standard threads					
0.9	I - I	B - B	J - J	B - Z	Z - Z	G - F
1.2	I - I	B - B	J - J	B - Z	Z - Z	G - F
1.7	I - I	B - B	J - J	B - Z	Z - Z	G - F
2.2	I - I	B - B	J - J	B - Z	Z - Z	G - F
2.6	I - I	B - B	J - J	B - Z	Z - Z	G - F
3.2	I - I	B - B	J - J	B - Z	Z - Z	G - F
3.8	I - I	B - B	J - J	B - Z	Z - Z	G - F
4.3	I - I	B - B	J - J	B - Z	Z - Z	G - F
4.9	I - I	B - B	J - J	B - Z	Z - Z	G - F
5.9	I - I	B - B	J - J	B - Z	Z - Z	G - F
6.5	I - I	B - B	J - J	B - Z	Z - Z	G - F
7.8	I - I	B - B	J - J	B - Z	Z - Z	G - F
9.8	I - I	B - B	J - J	B - Z	Z - Z	G - F

Table showing standard flange and thread combinations available in stock

Body (threads/flanges)															
	A		B		C		D		E		F		G
	H		I		J	Closed Body	Z								