

Klauke



**THE
REVOLUTIONARY
MICRO STRIP TOOL**



CUT



STRIP



CRIMP

THE MULTITALENTED KLAUKE MICRO

One tool for a wide range of applications

Cutting of various materials



Stripping



Crimping tools for cable end-sleeves



Crimping tools for cable lugs



Crimping tools for solderless terminals



Crimping tools for photovoltaic and compatible connectors



**ONE TOOL –
MANY APPLICATIONS**



THE NEW KLAUKE
STRIPPING DIES

REVOLUTIONARY IN THE MARKET



MICRO-STRIP

FASTER AND SAFER STRIPPING: USING THE STRIPPING DIES!

The **Klauke micro** also is a true all-rounder when it comes to stripping.

Using the stripping dies there is now, for the first time, an electromechanical tool available on the market for stripping conductors from 6 to 35 mm² cross-section.

Until now, users could only strip cables in the range up to 16 mm² by applying physical force – either with manual wire stripping tools or with a knife.


The advantages are obvious:

Compared to manual stripping with pliers, the **Klauke micro-strip** is much faster.

Compared to stripping using a knife, it is also much safer to work with.

Stripping dies for the Klauke micro

Cable diameter in mm ²	6	10	16	25	35
Article number	SD5006	SD5010	SD5016	SD5025	SD5035
Max. outer cable Ø OD in mm			Ø11.5		
Displacement DP in mm (fixed)			12		
Stripping length SL in mm (adjustable stop)			3 to 28		



Electromechanically effective: perfect results with only 20 % effort*

The drawback of manual stripping are well known: repeated use of the muscles in the forearm can lead to fatigue and overloading.

Stripping more than a hundred conductors in one day?

No problem with the micro!

Using the stripping dies, the Klauke micro becomes a tool that achieves consistently clean results – with considerably less force and significantly less strain on the joints.

*Compared to a hand tool.



STRIPPING

Stripping simply and safely -
No conductor damage



EKSD50ML

Electromechanical wire stripping tool

6 - 35 mm²



EKSD50ML

SCOPE OF SUPPLY

Art. no.	Description
SD5010	Stripping die for 10 mm ² conductor
SD5016	Stripping die for 16 mm ² conductor
SD5025	Stripping die for 25 mm ² conductor
SD5035	Stripping die for 35 mm ² conductor
SD50CS	Cable stop
KKEK50ML	Plastic carry case
KTG-H1	Tool grease
LGML1	Charger for 10.8 V Li-Ion rechargeable batteries, 230 V
RAML1225	Rechargeable battery 10.8 V / 2.5 Ah, Li-Ion (27 Wh)

SD5006, SD5010, SD5016, SD5025, SD5035

Stripping-crimping dies



SD5010
For 10 mm² conductor



SD5025
For 25 mm² conductor



SD5016
For 16 mm² conductor



SD5035
For 35 mm² conductor



SD5006
For 6 mm² conductor
(optionally available, not
supplied as standard)



SD50CS
Cable stop

Open for lots: the Klaue micro-strip creates a wide strip width

It might be impossible using wire strippers but it's no problem for the Klaue micro-strip: large cross-sections up to 35 mm² can also be stripped as well as thick insulation (NSGAFOU), double-insulated cable types plus harder and tougher insulation.

In many applications - for example in switch cabinet construction - stripping and cutting of cables are often completed simultaneously. By use of the integrated cutting die inside the stripping die, conductors of all classes can be cut, regardless of whether they are solid, stranded or fine-stranded.

Quick change from left to right-handed variant



Left-handed variant



Right-handed variant

Does your work team include left-handed and right-handed people?

Then no need to worry, with the Klaue micro-strip it's no problem.

The die can be used by both left- and righthanded people by changing the installation direction accordingly.

Details on the stripping function

The cutting cones are guided and connected by pins (screws) and pretensioned into the initial position by compression springs.

- When the tool is operated, the die bodies approach each other and the cutting cones cut into the cable.
- Further activation of the tool causes the cones to move axially and strip off the jacket.

The stripping length can be adjusted using the stop sleeve, thus ensuring consistent quality.



CRIMPING – CABLE END-SLEEVES

Perfect crimping results using crimping dies for cable end-sleeves



EKWF50ML

Electromechanical crimping tool

0.5 - 50 mm²



EKWF50ML

SCOPE OF SUPPLY	
Art. no.	Description
AE5071	Crimping die for cable end-sleeves, 0.5 - 6 mm²
AE5072	Crimping die for cable end-sleeves, 10 - 25 mm²
AE5073	Crimping die for cable end-sleeves, 35 - 50 mm²
ZAE5072	Crimping die for twin cable end-sleeves, 2x6 - 2x16 mm²
KKEK50ML	Plastic case
LGML1	Charger for 10.8 V Li-Ion rechargeable batteries, 230 V
RAML1225	Rechargeable battery 10.8 V / 2.5 Ah, Li-Ion (27 Wh)

AE5071, AE5072, AE5073, ZAE5072

Including cable end-sleeves crimping dies



AE5071
for cable end-sleeves
0.5 - 6 mm²



AE5072
for cable end-sleeves
10 - 25 mm²



AE5073
for cable end-sleeves
35 - 50 mm²



ZAE5072
for twin cable
end-sleeves
2x6 - 2x16 mm²

CRIMPING – INSULATED CONNECTORS

Highly versatile



EK50ML

Electromechanical crimping tool

0.14 - 50 mm²



EK50ML

SCOPE OF SUPPLY	
Art. no.	Description
IS5071	Crimping die for insulated connectors 0.5 - 6 mm²
KKEK50ML	Plastic case
LGML1	Charger for 10.8 V Li-Ion rechargeable batteries, 230 V
RAML1225	Rechargeable battery 10.8 V / 2.5 Ah, Li-Ion (27 Wh)

IS5071

Crimping die included



IS5071
For insulated Connector
0.5 - 6 mm²

**CRIMPING - photovoltaic connectors
and compatible connectors**



EKPV50ML

Electromechanical crimping tool
2,5 - 6 mm²

PV502
Crimping die inclusive



PV502
Crimping die



EKPV50ML

SCOPE OF SUPPLY	
Art. no.	Description
PV502	Crimping die
KKEK50ML	Plastic case
LGML1	Charger for 10.8 V Li-Ion rechargeable batteries, 230 V
RAML1225	Rechargeable battery 10.8 V / 2.5 Ah, Li-Ion (27 Wh)

CUTTING
One die - countless
possibilities



EC50ML

Electromechanical cutting tool
0,5 - 50 mm²

S502
cutting die inclusive



S502
Cutting dies



EC50ML

SCOPE OF SUPPLY	
Art. no.	Description
S502	Cutting dies
KKEK50ML	Plastic case
LGML1	Charger for 10.8 V Li-Ion rechargeable batteries, 230 V
RAML1225	Rechargeable battery 10.8 V / 2.5 Ah, Li-Ion (27 Wh)

THE REVOLUTIONARY POWERSENSE FUNCTION

What makes the Klaue micro so unique is its innovative operating concept with PowerSense function. Workpiece pre-clamping is done by hand – with the familiar precision and speed of mechanical crimping pliers. The stripping, cutting or crimping operation is performed automatically using the force of the integrated motor.



Best crimping results



Ready whenever you need it




Manual pre-clamping



Motorized stripping / crimping / cutting

OUR VERSATILE DIES AT A GLANCE



Stripping dies

SD5006, SD5010, SD5016, SD5025, SD5035
6 - 35 mm²

Crimping dies for
cable end-sleeves

AE5071 0.5 - 6 mm²

Crimping die for
insulated connectors

IS5071 0.5 - 6 mm²

AE5072 10 - 25 mm²

AE5073 35 - 50 mm²

Cutting die

S502

PV502

2.5 - 6 mm²

ZAES072 2x 6 - 2x 16 mm²
for twin cable end-sleeves

All compatible dies
of the K50 series
can be found here:

**K50
SERIE**



GOES EASY ON THE NERVES – IN THE TRUEST SENSE OF THE WORD



Frequent manual crimping:

leads, in the long term, to repetitive strain injuries in the wrist and forearm.



Motorized crimping with innovative PowerSense function:

ensures maximum efficiency with low strain and minimum health risk.

The enormous easing of the burden on nerves and muscles thanks to the PowerSense function is particularly worthwhile when you consider the costs that can arise from lost working time of employees, for example due to carpal tunnel syndrome.

- Fewer symptoms of stress overloading
- Less lost working time and fewer delays in schedule
- Greater planning security for everyone

INNOVATIVE TECHNOLOGY - OPTIMUM RESULTS

Thanks to its lightweight design and size, the tools of the Klaue ML family are the ideal tools when working in confined spaces, thereby speeding up and simplifying the work to be done. Equipped with a 2.5 Ah rechargeable battery, one charge easily suffices to get the job done for an entire working day. The Klaue micro is the perfect supplement to the Klaue ML family portfolio.



EKWF120ML



EK30IDML



EK50ML



ES32ML



EK354ML

MICRO COMPACT
AND HANDY



Versatile
for convenient stripping,
crimping and cutting

**Ultra-light
and ergonomic**
so that operators' most
valuable assets – their
hands* – stay healthy always



Illuminating
thanks to its LED lamp for
illuminating the crimping location
and the working area



**Balanced
and drop-safe**
thanks to the tool fixing point
for use with balancer or to
ensure drop protection when
used in field work



Innovative
thanks to single-lever operation
for controlling all tool functions



Smart and rugged
with multifunction LED for
maintenance display and
data transmission as well as
powerful Li-Ion rechargeable
battery with state-of-charge
indicator

TECHNICAL DATA EK 50 ML

Battery voltage	10.8 V
Battery capacity	2.5 Ah, Li-Ion
Battery charging time	ca. 45 min.
Weight with Battery	0.96 kg
Ambient temperature	-10 °C to +40 °C

L-BOXX WITH ELECTROMECHANICAL CRIMPING TOOL
EK 50 ML AND EXTENSIVE ADDITIONAL EQUIPMENT

LBOXXEK50ML

SCOPE OF SUPPLY		
Art. no.	Description	Quantity
3R8	Tubular cable lug without inspection hole, 16 mm², M8, Cu tin-plated	25
47612	Insulated Cable end-sleeves, 10 mm², 22 mm	50
47712	Insulated Cable end-sleeves, 16 mm², 24 mm	50
47818	Insulated Cable end-sleeves DIN 46228 Part 4, 25 mm²	25
47918	Insulated Cable end-sleeves DIN 46228 Part 4, 35 mm²	25
48025	Insulated Cable end-sleeves DIN 46228 Part 4, 50 mm², 40 mm length	20
4R8	Tubular cable lug without inspection hole, 25 mm², M8, Cu tin-plated	25
65206	Insulated Solderless terminal M6, 10 mm², fork type	50
AE5072	Crimping dies for cable end-sleeves, 10 - 25 mm²	1
AE5073	Crimping dies for cable end-sleeves, 35 - 50 mm²	1
EK50ML	Electromechanical crimping tool 0.14 - 50 mm²	1
IS5072	Crimping dies IS 50, simple crimping, 10 - 16 mm²	1
K118	Manual cutting tool for Al- and Cu cables up to Ø 12 mm	1
LBOXX136LFG	L-BOXX with front handle (B/T/H: 442 x 357 x 151 mm)	1
LGM11	Charger for 10.8 V Li-Ion rechargeable batteries, 230 V	1
R505	Crimping dies R 50, 16 - 25 mm²	1
RAML1225	Rechargeable battery 10.8 V / 2.5 Ah, Li-Ion (27 Wh)	1





RIDGID

GREENLEE

Klauke

To receive up-to-date information on our products, services and promotional campaigns, register for our Newsletter here:

[KLAUKE.COM/NEWSLETTER](https://klauke.com/newsletter)



Follow us!



© 2024 Gustav Klauke GmbH. All rights reserved. The Klauke logo and the Emerson logo are registered trademarks of Emerson Electric Co. or its subsidiaries in the USA and other countries. All other marks belong to their respective owners. Subject to change without notification. BREX50MLGB 07/24 III

Klauke

Gustav Klauke GmbH
Auf dem Knapp 46
D-42855 Remscheid

Tel.: +49 (0) 2191 / 907 - 0
Klauke-Info@Emerson.com
[Klauke.com](https://klauke.com)

EMERSON