

GITRALINOX



Anti-bellier - Anti-water hammering



Vases sanitaires - Sanitary vessel

Les vases GITRALINOX en acier inoxydable sont destinés à des milieux agressifs ou dont le niveau d'hygiène est une exigence de premier ordre. Ils sont adaptés à l'agro-alimentaire, pour des systèmes à eau froide et pour la production d'eau chaude sanitaire. Certains sont également utilisés comme anti-coup de bélier (réf. AB 0.16). Cette gamme devient progressivement incontournable du fait de sa longévité exceptionnelle. Elle se distingue par la qualité de sa membrane en butyle alimentaire. L'attestation de Conformité Sanitaire ACS et la norme anglo-saxonne WRAS, garantissent l'usage des vases GITRALINOX pour la production d'eau potable.

The GITRALINOX vessels are made of stainless steel.

They are meant to sanitary hot water production, against water hammering (AB 0.16 code) or in ordinary cold water installations.

They are particularly adapted to corrosive atmospheres (coastal areas, food-industry etc.) The GITRALINOX vessels have become most popular because of their long-life resistance.

These vessels have an absolutely non-toxic membrane suitable for potable water, certified by the French norm ACS and the British WRAS (WRAS).

VASE À MEMBRANE FIXE - FIXED MEMBRANE

Code - Article	Reference	Volume (litre)	Dimensions - Dimensions		Raccord Water connection (male)	Pression maxi Max. working pressure (bar)	Pression de gonflage Range of precharge pressure bar
			A	H			
11B000AA23	AB 0.16	0,16	82	114	1/2"	15	3,5
11B000BB03	AB 0,5	0,5	94	160	1/2"	10	3,5
11B0000108	AB 1	1	116	197	1/2"	10	0,5
11B0000206	AB 2	2	140	238	1/2"	10	3,5
11B0000802	AB 8	8	198	321	3/4"	10	2,5
11B0001203	AB 12	12	270	323	3/4"	10	2,5
11B0001803	AB 18	18	270	406	1"	10	2,5

VVEF+BK



Code Article	Reference	Capacité Capacity (litre)	Raccord Water connection (male)	Pression gonflage Standard setting precharge pressure	Pression maxi Max. working pressure (bar)
11H0001206	VVEF12+BK	12	3/4"G	2,5	10
11H0001908	VVEF19+BK	19	3/4"G	2,5	10
11H0002405	VVEF24+BK	24	3/4"G	2,5	10

GS + BK



Code Article	Reference	Capacité Capacity (litre)	Manchon Water connection Ø R	Pression gonflage Standard setting precharge pressure	Pression maxi Max working pressure (bar)
11GS001202	GS12+BK	12	3/4"	2,5	10
11GS001902	GS19+BK	19	3/4"	2,5	10
11GS002402	GS24+BK	24	3/4"	2,5	10