

Accessories, to be ordered separately

**IH-A 24630, IH 42630**

Insulating hood, of flexible rubber with outer conductive layer and a preinstalled insulating rod. To be mounted on the bushing in a switchgear or a transformer 630 A to insulate it when a cable is temporarily disconnected but other cables are energized.

**PSSK**

Screen separation kit to achieve a metallic screen on each core for 3-core cable.

**CSAP-A**

Surge arrester, 630 A.

**CSEP-A**

Parallel cable connector.

**IP 630**

Screened insulating plug for installation in the connector so that the cable can be energized even when disconnected from the switchgear or transformer 630 A.

**TSH**

Branch seal kit to achieve a sealing on each core for 3-core cable.

**PG 630**

Bushing for voltage testing.

**JPB 630**

Universal earthing device with two fields of application for 630 A and 12-42 kV:

- As earthing-for-work device mounted at the back of a connected cable connector CSE-A for 630 A.
- As short-circuit protective earthing mounted in front of a disconnected cable connector CSE-A for 630 A.

**PC 630/250**

Parallel coupling piece. Replaces the plug in CSE-A 630 A when making a parallel connection to CSE-A 250 A. Delivered in 3-phase kits and hex bit socket.

**MA-A 630**

Measurement adapter used for mega ohm Ω measurements and to perform different measurements up to 5 kV DC, for example determination of phases, 630 A.

**PG-A 630**

Bushing for voltage testing, 36 – 42 kV.

**JPA V**

Tool for earthing device, JPB 630.

Designation	Description	Qty. per kit	Weight kg/kit	See page
IH-A 24630	Insulating hood, 12 – 24 kV, 630 A	3	5.2	33
IH-A 42630	Insulating hood, 36-42 kV, 630 A	3	5.5	33
IP 630	Screened insulating plug, 630 A	1	2.2	33
PC 630 / 250	Parallel coupling piece	3	3.0	33
PSSK	Screen separation kit, heat-shrink for 3-core cable	1	1.0–1.1	54
TSH	Branch seal	1	0.3–1.0	55
MA-A 630	Measurement adapter, 630 A	3	0.2	33
CSAP-A	Surge arrester, 630 A, 12 – 24 kV	1	3.6–5.0	35
PG 630	Bushing for voltage testing, 630 A, 12 – 24 kV	1	1.5	33
PG-A 630	Bushing for voltage testing, 630 A, 36 – 42 kV	1	2.0	33
CSEP-A	Parallel cable connector	1	5.7–9.8	34
JPB 630	Earthing device, 630 A	1	5.0	33
JPA V	Tool for earthing-for-work device, JPB 630	1	1.8	33