
Revisão	Descrição	Aprovação	Data







OUTLET DUPLEX

CODE: **GF20BKLA**
MANUFACTURE: BRYANT
COLOR: BLACK

DESCRIPTION:
FLUSH, NYLON FACE BACK & SIDE WIRE MULTIPLIPLE DRIVE SCREWS.
MATCHING NYLON WALLPLATE INCLUDED.

ESPECIFICATIONS:
TRIP LEVEL: 4 TO 6 mA
TRIP TIME: 025 SEC. NOMINAL
FREQUENCY: 60HZ
VOLTAGE: 110AC + 10% - 15%
AMPERAGE: 15A / 20A FEED THRU:
Terminal Accommodations:14-10 AWG
MAXIMUM INTERRUPTING CAPACITY: 10000A
OPERAGE TEMPERATURE : -35°C TO +66°C
MAXIMUM HUMIDITY: 95%
LISTINGS STANDARDS: UL498 / UL493 2003 / UL FILE E4 1978 / CSA CERTIFIED.

Eng Qualidade:	Eng. Produção		
Baseado em	Num. Registro	Título: **OUTLET**	
Elaborado por: R.Nilo 11/12/15	Departamento Responsável: PPTR	**OUTLET DUPLEX GF20BKLA 110VAC 60HZ**	
Aprovado por: R.Vasconcelos	Departamento Emitente		Língua: En
Revisão		**E-1553025**	Pagina: 1
ABB		Núm. Documento: **1ZXY029680-TWE**	Total: 1

Revisão	Descrição	Aprovação	Data

Eng Qualidade:	Eng. Produção		
Baseado em	Num. Registro	Título	
Elaborado por R.Nilo 11/12/15	Departamento Responsável PPTR	**OUTLET**	
Aprovado por R.Vasconcelos	Departamento Emitente	**OUTLET DUPLEX GF20BKLA 110VAC 60HZ**	Língua En
Revisão		**E-1553025**	Pagina 2
ABB		Núm. Documento **1ZXY029680-TWE**	Total. 1