

Dokument Nr. 1040600TD1
Document No.

Artikelnummer Item number	1040600
Bezeichnung	Kraftmessachse Typ 0201; 0...30 t
Description	Force measuring pin
Messbereich Measurement range	0...30 t
Ausgangssignal Output signal	CANopen Safety
Nennlast Nominal load	25 t
Grenzlast Max. load	150 %
Bruchlast Breaking load	300 %
Nicht-Linearität Non-linearity	0,5 % FS
Relative Hysterese Relative hysteresis	2 % FS
Verstärkertyp Amplifier type	DANGmicro CANopen
Node ID 1	0x0A
Node ID 2	
Bitrate	125 kbit/s
Performance level	PL d
Zul. Brückendiff. Accept. bridge deviation	3,4 % FS
Schutzart Protection class	IP66/ IP67
Redundanz Redundancy	
Betriebstemperatur Operating temperature	-40...80 °C
Ex-Schutz Ex-protection	

Flanschstecker / -dose 5-polig /
Male / Female connector 5-pole:
M 12x1
A-kodiert / A-coded

incl. Staubschutzkappe /
Protection cap included
Belegung / Configuration:

1 = Schirm/Shield
2 = CAN 9...36 V DC
3 = CAN GND
4 = CAN H
5 = CAN L