

D7/C Series Nuova General Instruments Pressure Relief Valve - Piped Outlet

Model D7/C Series Nuova General Piped Outlet Pressure Relief Valve.

The Nuova General Instruments range of safety valves are approved and comply with the requirements of the European Directive 97/23/EC (PED) and ASME V111 Div.1. On request testing can be performed by most authorities such as TUV, RINA, Bureau Veritas, ABS and Lloyd's Register. ATEX certification is also optionally available on many models.

In September 2016 Ashford Instrumentation Ltd were confirmed as a reseller of the Nuova General Range of Pressure Relief Valves.

Technical Note - Hygienic connection options are only available on stainless steel body versions of this valve.



Outlet	Piped
Model D7/C	D7C - With Ring Nut
Model D7/CS	D7/CS - Without Ring Nut
Orifice	7mm
Threaded Inlet Connection	1/4" & 3/8" BSP, BSPT or NPT
Threaded Outlet Connection	1/2" BSP
Hygienic Inlet Connection	3/4" Tri-Clamp
EU Setting Range	300 Millibar to 60 Bar (PN 60 Rated)
USA & Can. Setting Range	1 Bar to 40 Bar (PN 40 Rated)
Body	Brass, Stainless Steel or S/S Brass Mixed
Spring	Alloy Steel
Seat Seals	NBR, EPDM, Viton, Silicone, PTE, Kalrez
EU Homologation	E.D. 2014/68/UE IV Cat.(PED), EAC
USA & Can. Homologation	ASME VIII Div.1 & Canadian Reg. CRN
ATEX	Ex II 2D c, Ex II 2G c

