
Supco
WIRELESS VACUUM GAUGE
0
ATM
230
Micron
VG640TL
SET
MUTE
UNITS
POWERED BY
SUPCO
TECHLINK
www.supco.com

PRODUCTIVITY ELEVATED.

WIRELESS VACUUM GAUGE
VG640TL

Technicians can now use the power of their mobile device along with the free Supco® Techlink™ App to enhance job-site productivity while working with a precision digital vacuum gauge.

The Supco® Techlink™ VG640TL allows for real-time remote Bluetooth® monitoring from up to 200 ft away with a mobile device and reporting of the evacuation process, which can be downloaded to PDF and Excel/CSV formats.

With a revolutionary contaminant resistant *Lifetime Sensor* and an unmatched resolution as low as .5 Micron, the VG640TL can be used as a standalone gauge or wirelessly paired with a mobile device for access to a convenient suite of remote features for today's technician.

FEATURES

- Easy to use - configure in seconds with an iOS® or Android® device
- Contaminant & oil resistant *Lifetime Sensor*
- Bluetooth® Low Energy (BTLE) standard (v4.1)
- Display resolution: As low as 0.5 Micron
- Standard 1/4" Male Flare Fitting
- Vacuum Range: 0 - 19000 Micron (0 - 2600 Pascal)
- Units: Micron, milliBar, Pascal, Torr, milliTorr
- Accuracy: +/-7% or +/-10 Micron (1.3 Pascal), whichever is larger (50 to 2000 Micron) at 75°F (24°C)
- Instant warm-up and response time
- Large, back-lit LCD display
- Temperature compensated for accuracy
- Auto power-off function
- Battery life up to 400 hours continuous use
- Includes vacuum gauge coupler, convenient magnetic holding strap & Quick Start guide





SUPCO® TECHLINK™ DIAGNOSTIC APP

- Remote Bluetooth® monitoring from up to 200 ft away
- Real time viewing & logging with graphs
- Low & high vacuum alerts
- Record & export the evacuation process to PDF and Excel / CSV formats
- Time evacuation & vacuum decay process

Learn more and download

SUPCOTECHLINK.COM

Download on the App Store | ANDROID APP ON Google play