

# Product sheet



ARTEOR LEGRAND

Arteor Socket - US - 15 A / 127 V - 2P+E - 2 modules - white

REF. 572117 | EAN. 3245065721171

No price to display

> [Visit e-catalogue](#)

### Product charateristics

- Arteor™ - international socket outlets - Mechanisms supplied with rocker plates , to be equipped with support frames and plates
- American type socket outlets 15 A - 127 V2P+E - 2 modules - White

### Technical characteristics

|                                     |                                        |
|-------------------------------------|----------------------------------------|
| Model                               | US/CA (NEMA 5-15) (type B)             |
| Protective contact                  | Other                                  |
| Number of active contacts (round)   | 1                                      |
| Number of active contacts (flat)    | 0                                      |
| Assembly arrangement                | Basic element with central cover plate |
| With complementary luminous signal  | No                                     |
| Number of ports USB-A               | 0                                      |
| Number of ports USB-C               | 0                                      |
| Number of socket outlets            | 1                                      |
| Socket outlets phase-separated      | No                                     |
| Number of modules (module system)   | 2                                      |
| Number of socket outlets switchable | 0                                      |
| Number of phases                    | 1                                      |
| Imprint/indication                  | Other                                  |
| Connection type                     | Screwed terminal                       |
| With hinged lid                     | No                                     |
| With enhanced contact protection    | No                                     |

|                                        |               |
|----------------------------------------|---------------|
| Material quality                       | Thermoplastic |
| Halogen free                           | Yes           |
| Surface protection                     | Untreated     |
| Surface finishing                      | Glossy        |
| Antimicrobial treatment                | No            |
| With loop through function             | Yes           |
| With on/off switch                     | No            |
| Colour of switch operator              | White         |
| Rotated central insert                 | No            |
| Nominal current                        | 15 A          |
| Nominal voltage                        | 127 V         |
| Frequency                              | 50-60 Hz      |
| Suitable for degree of protection (IP) | IP40          |
| degree of impact strength (IK)         | IK04          |
| Device width                           | 45 mm         |
| Device height                          | 45 mm         |
| Device depth                           | 35.3 mm       |

|                                 |                            |
|---------------------------------|----------------------------|
| Label space/information surface | No                         |
| Colour                          | White                      |
| RAL-number (similar)            | 9003                       |
| Metallic colour                 | No                         |
| Transparent                     | No                         |
| Lockable                        | No                         |
| Eject-mechanism                 | No                         |
| Insulated mounting              | No                         |
| With function lighting          | No                         |
| Overvoltage protection          | No                         |
| Fault current protection        | No                         |
| With miniature fuse             | No                         |
| Special power supply            | None                       |
| Mounting method                 | Module frame               |
| Type of fastening               | Snap mounting (engagement) |
| Material                        | Plastic                    |

|                                       |                     |
|---------------------------------------|---------------------|
| Compatible with Apple HomeKit         | No                  |
| Compatible with Amazon Alexa          | No                  |
| Compatible with Google Assistant      | No                  |
| IFTTT support available               | No                  |
| With Wi-Fi signal repeater            | No                  |
| With built-in bluetooth speaker       | No                  |
| For heavy conditions according to VDE | No                  |
| Built-in depth                        | 26.8 mm             |
| Operating / setting temperature       | -5-50 °C            |
| Storage temperature                   | -10-70 °C           |
| Voltage type                          | AC                  |
| Power Delivery                        | No                  |
| Cable nature for connection           | Flexible or rigid   |
| Cable section                         | 4-4 mm <sup>2</sup> |
| Cable support                         | Other               |
| Connected object                      | No                  |

## Documentation

### TECHNICAL DOCUMENTATION

 F00723EN-05.pdf | PDF (1.07Mo)

### Agreements & Certificates

 OC / CB-FR\_713123 | (0.62Mo)

### CAD & Design specs / BIM

 3D\_LG-572117.stp | IFC (1.98Mo)