

HOW TO ORDER A COMPLETE FILTER HF 502

	1		2		3		4		5		6		7		8	
HF502-	20.122	-	AS	-	FG010	-	B17	-	GG	-	B	-	H	-	Z	-
	9		10		11		12		13		14					
	XA	-	GA	-	M	-	YD	-	GE	-	K					

1	Filter type	CODE
	See table from pag. 23 to pag. 26	HF502..

2	Filtering surface	CODE
	Standard	AS
	Oversize	FS

3	Degree of filtration	CODE
3	[μm] Micro-fibre glass	FG003
6	[μm] Micro-fibre glass	FG006
10	[μm] Micro-fibre glass	FG010
25	[μm] Micro-fibre glass	FG025
25	[μm] Stainless steel wire mesh	MI025
60	[μm] Stainless steel wire mesh	MI060
125	[μm] Stainless steel wire mesh	MI125
90	[μm] Steel wire mesh	MS090
10	[μm] Cellulose	SP010
25	[μm] Cellulose	SP025
10	[μm] Reinforced cellulose	RP010
25	[μm] Reinforced cellulose	RP025

4	By-pass setting valve	CODE
	With By-pass setting valve 25 [psi] (1,7 [bar])	B17
	With By-pass setting valve 51 [psi] (3,5 [bar])	B35

5	Inlet port	CODE
	GAS threads (BSPP)	
	G 3/8	GC
	G 1/2	GD
	G 3/4	GE
	G 1	GF
	G 1 1/4	GG
	G 1 1/2	GH
	G 2	GL
	NPT threads	
	3/8	NC
	1/2	ND
	3/4	NE
	1	NF
	1 1/4	NG
	1 1/2	NH
	2	NL
	SAE threads ODT	
	3/8	OA
	1/2	OB
	3/4	OD
	1	OF
	1 1/4	OG
	1 1/2	OH
	2	OI

6	Seals	CODE
	Buna	B
	Viton	V

7	Filler cap	CODE
	Without	H
	With filler cap (except HF502-10)	L

8	Magnetic set	CODE
	Without	Z
	With magnetic set	R

9	Indicators arranged	CODE
	Without	XN
	On the housing - right (1) (except HF502-10 and HF502-30)	XA
	On the housing - left (2)	XB
	On the cover (3)	XD

10	Indicator's ports dimensions	CODE
	GAS Threads (BSPP)	
	G 1/8	GA
	G 1/8 with plug	DA

11	Indicators	CODE
	Without	G
	Manometer - rear connection	M
	Manometer - radial connection	N
	Visual indicator	P
	Electrical indicator	S

12	Secondary ports	CODE
	Without	YN
	On the housing - right (1) (except HF502-10 / 20 / 30)	YA
	On the housing - left (2) (except HF502-10 / 20 / 30)	YB
	On the housing - front-left (5) (only for HF502-30)	YC
	On the cover (4)	YD

13	Secondary ports dimensions	CODE
	G 3/8	GC
	G 1/2 (except HF502-10)	GD
	G 3/4 (except HF502-10)	GE
	G 1 (only for HF502-40)	GF
	G 1 1/4 (only for HF502-40)	GG

14	Accessories	CODE
	Without	K
	With diffuser	D
	With bowl extension(ex. bowl extension length 150=P150)	P...
	With level dipstick(ex. level dipstick length 175=L175)	L...

☒ Standard ☐ On request