


Ausführung construction	Y - Verbinder Y - connector
Werkstoff material	Polyamid 6, UL94 V0 polyamide 6, UL94 V0
Temperatur temperature	-40°C - +105°C
Schutzart protection	IP66 / IP68 / IP69K
gemäß according to	IEC EN 61386



* = B =  * = G = 



Y-Verteiler / Y-connector

Art. Nr. IP66 art. no. IP66	Art. Nr. IP68/69K art. no. IP68/69K	NW DN	L mm	W mm	E mm	VPE Stk. unit pcs.
Y6*100707	Y8*100707	10-07-07	69,4	35,0	21,0	20
Y6*121010	Y8*121010	12-10-10	74,0	41,0	26,0	20
Y6*171212	Y8*171212	17-12-12	82,5	49,0	32,0	20
Y6*231717	Y8*231717	23-17-17	96,0	61,0	40,0	20
Y6*292323	Y8*292323	29-23-23	112,0	77,0	48,0	10
Y6*362929	Y8*362929	36-29-29	130,0	92,0	58,0	5
Y6*483636	Y8*483636	48-36-36	148,5	115,0	70,0	5

Wellrohrverteiler-Anschlussarmatur Typ Y zur Aufteilung eingehender Leitungen. Durch die parallel verlaufenden Ausgänge in Richtung der Eingehenden Leitung, können Kabel und Litzen problemlos eingeführt und durch die Armatur gezogen werden. Geeignet für normale Anforderungen in technischen oder Elektroinstallations-Anwendungen, insbesondere für erhöhte Anforderungen in Industrie und Bahntechnik bei gleichzeitiger Abdichtung über das Wellrohr von bis zu IP69K.

Distribution fitting type Y is conceived to divide conductor bundles into multiple conduit lines. Available with one large conduit entry and two smaller conduit exits. Due to the parallel outlets in line with the inlet direction, wires and cables can be easily pulled through the fitting. Suitable to standard requirements in industrial and electro technical installation applications as well as for increased requirements in heavy industry and railway applications also provide complementary liquid and tightness at the conduit itself until to IP69K..

