# D-Sub25 male to Terminal Block Adapter with Enclosure

## Description

This terminal block adapter by Delock can be used to connect bare wires. Thus the adapter is not only convenient for special industry applications, but also for the hobby area, e.g. railway modelling.

**Protection by enclosure**
The plastic enclosure protects the PCB from dirt and damage.

**Strain relief**
The integrated strain relief fixes the cable in the enclosure.

**Item no. 66266**

EAN: 4043619662661

Country of origin: China

Package: Zip poly bag

## Technical details

- Connectors:
  1 x Parallel DB25 male with nuts
  1 x 26 pin terminal block
- Pin assignment: 1:1
- Pitch 1 - 16 pins: 5.00 mm
- Pitch 17 - 26 pins: 3.81 mm
- Useable for a cable gauge from 26 to 18 AWG
- Operating temperature: -20 °C ~ 105 °C
- Dimensions (LxWxH): ca. 64.8 x 56.4 x 25.0 mm

## System requirements

- A free DB25 female

## Package content

- Adapter
- 1 x strain relief

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

- 2 x locking screws

## Images

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**

## Interface

| | |
|---|---|
| Connector 1: | 1 x Parallel DB25 male with nuts |
| Connector 2: | 1 x 26 pin terminal block |

## Technical characteristics

| | |
|---|---|
| Operating temperature: | -20 °C ~ 105 °C |

## Physical characteristics

| | |
|---|---|
| Pitch distance: | 1 - 16 pins: 5.00 mm<br>17 - 26 pins: 3.81 mm |
| Cable gauge: | 26 - 18 AWG |
| Length: | 64.8 mm |
| Width: | 56.4 mm |
| Height: | 25.0 mm |

### Manufacturer information

| | |
|---|---|
| Street | Beeskowdamm 13/15 |
| Postal code | 14167 |
| City | Berlin |
| Country | Deutschland |
| E-Mail | info@delock.de |
| Website | www.delock.de |

All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted. **© 2026 by Delock. All rights reserved.**