

Redwing® Fuel Oil



Product Specifications

Application

Redwing® Fuel Oil is for transfer and delivery of fuel oil and petroleum products for home delivery, commercial and industrial service. Redwing Fuel Oil has two textile braids. The braided construction reduces kinking and twisting when reeling. The smooth cover has low drag resistance.

Construction Tube

Nitrile synthetic rubber (ORS), ARPM Class A (High Oil Resistance)

Cover

Red Chemivic™ synthetic rubber (smooth finish) (ORS)

Reinforcement

Two Braided (2) synthetic yarn

Temperature Range

-40 °F to 140°F (-40°C to 60°C)

Redwing® Fuel Oil

Packaging

Reels, cut lengths, and coupled lengths

Branding

Example: 1" (25.4mm) 2 BD Redwing® Fuel Oil Continental ContiTech Made in U.S.A.

Couplings

Coupled assemblies available.

Order Codes

532-016

SAP#	ID		Nom. OD		Max WP		Weight	
	in.	mm	in.	mm	psi	MPa	lb./ft.	kg/m
20021667	1	25.4	1.50	38.1	250	1.72	0.57	0.85
20021681	1¼	31.8	1.80	45.7	250	1.72	0.65	0.97
20021708	1⅜	34.9	1.88	47.8	250	1.72	0.70	1.04
20021735	1½	38.1	2.10	53.3	150	1.03	0.92	1.37

Hose design factor 4:1