



Impuls-Magnetventil NAMUR, 5/3-Wege, NPT1/4, Aluminium

Bistable solenoid valve NAMUR, 5/3-ways, NPT1/4, Aluminum

Artikelnummer Part number	MNI53115AC-MSG-NPT
Arbeitsdruck/Durchfluss Air pressure/Flow rate	2-10bar, 1250 l/min
Spannung/Leistung Voltage/Power consumption	115V AC, 5VA
IP-Schutz IP protection	IP67
SIL Level SIL level	
Umgebungstemperatur Ambient temperature	-10...+50°C
Elektrischer Anschluss Electric connection	M16x1,5 (4-8mm)
Medium Medium	Gereinigte, geölte / nicht-geölte Druckluft (Stufe 5 nach ISO 8573-1) Cleaned, lubricated / non-lubricated compressed air (Level 5 acc. to ISO 8573-1)

Schaltbild Diagram



Maßzeichnung Dimensions

Enthaltenes Zubehör Included Accessories

-ES115AC	Magnetspule, 115V AC, 5VA, 50-60Hz, 125mA, Form B Magnet coil, 115V AC, 5VA, 50-60Hz, 125mA, Form B
-GS	Gerätestecker (Industrieform B) Plug connector (Industry form B)

Besonderheiten Extras

- Mittelstellung geschlossen - Center position closed
--