

## Accessories, to be ordered separately

### Premolded cable joint, SOJ 12–36 kV

#### Diffusion seal, WIM

Used as complement to SOJ CS, SOJ CSS or SOJ R when jointing 1- or 3-core watertightened cables with diffusion barrier of aluminium.




WIM 3

| Designation | Fitting joint                                                                                                                                       | Type of cable                                     | Weight<br>kg/kit |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|------------------|
| WIM 3       | SOJ 121–3, 122-3, 123-3<br>SOJ 241–3, 242-3, 243-3<br>SOJ 361-3, 362-3, 364-3                                                                       | 3-core with Al foil in direct contact with screen | 0.5              |
| WIM 5       | SOJ 121-1, SOJ 122-1                                                                                                                                | 1-core with Al-foil in direct contact with screen | 0.4              |
| WIM 6       | SOJ 123-1, SOJ 124-1, SOJ 125-1<br>SOJ 241-1, SOJ 242-1, SOJ 243-1<br>SOJ 244-1, SOJ 245-1, SOJ 361-1<br>SOJ 362-1, SOJ 363-1, SOJ 364-1, SOJ 365-1 | 1-core with Al-foil in direct contact with screen | 0.4              |

#### Accessories, to be ordered separately



ADAPTER



TS



WIM



STOP



SH-SKRM

#### To be ordered separately

| Accessories | Description                                                    | CSS | CS | R | SL | RWI | RWIT | HSTS | See page |
|-------------|----------------------------------------------------------------|-----|----|---|----|-----|------|------|----------|
| ADAPTER     | Cables with different dimensions                               | X   | X  | X | X  | X   | X    | X    | 3/36     |
| TS          | Additional kit for sector shaped 3-core cables                 | X   | X  | X | X  | –   | X    | X    | 3/36     |
| WIM         | Diffusion seal                                                 | X   | X  | X | –  | –   | –    | X    | 3/37     |
| STOP        | Crutch seal when 3 x 1-core cables are jointed to a 3-core     | –   | –  | X | –  | –   | –    | –    | 3/36     |
| SH-SKRM     | Bolt connector                                                 | X   | X  | X | X  | X   | –    | X    | 3/51     |
| JSA 10–13   | Earthing kit for cable with Cu-tape screen                     | X   | X  | X | –  | –   | –    | X    | 3/48     |
| JSA 14–16   | Earthing kit for cable with Al-foil screen only                | X   | X  | X | –  | –   | –    | X    | 3/48     |
| ARM         | Armoured cable or when extra mechanical protection is required | –   | –  | – | X  | –   | –    | –    | 3/49     |