Type of Valve	:	3/2 Spring Return Direct acting Universal Valve
Ordering Code	:	30334-5-2R-B2+III-24V-AC/DC-39-FR-H-01
Item Code	:	93000021750
Port Connection	:	1/4" NPT(F)
Orifice Size (mm)	:	5 mm
Flow Factor (kv)	:	8 LPM
Body Material	:	Extruded Brass with internal wetted parts of Brass, Stainless Steel 316
Manual Override	:	Manual Override Not Provided
Seat Seal Material	:	NBR
Media	:	Air, Clear Water
Main Pressure	:	0 - 10 bar
Media Temp Range	:	-25°C to +75°C
Type of Solenoid	:	Flameproof Enclosure Ex d having integrated Terminals, Horizontal Cable Entry M20X1.5mm (F)
Size of Coil	:	III
Enclosure Material	:	Aluminium Cast Epoxy Powder coated
Special Version	:	Inbuilt Full Rectifier with Surge Suppressor
Voltage	:	24V 50Hz/ 60Hz/ DC (-10%, +10%)
Power of Coil	:	8 W
Insulation Class	:	Class H
Approval	:	CE - ATEX
Coil Certificate nr.	:	ATEX TI22ATEX 278X
Marking	:	Ex II 2GD Ex db IIC T6/ T5 Gb Ex tb IIIC T80°C/ T95°C Db, IP66/ IP67 -40 °C < Ta < 60 °C FOR T6 -40 °C < Ta < 70 °C FOR T5

Created By: Sumit Rawat Print Date And Time: 10/03/2026 16:31

This is System Generated Report