

FLAIRMO OX COMBI FILTER



The FLAIRMO OX Combi Filter have incorporated several unique design features to minimise differential pressure and provide a filter and element combination where the differential pressure starts low and stays low to maximise energy savings and provide the lowest lifetime costs without compromising air quality.

Specifications

Part No.	17131000
Filter-Type-1	Coalescing, 0.01 mg/m ³ - 0.01 ppm @ 21°C
Filter-Type-2	Oil Vapour Removal, 0.003 mg/m ³ - 0.003 ppm @ 21°C
Replacement Filter Element Part No.	Filter type 1 (17131002), Filter type 2 (17131707)
Maximum Flow Rate	400 l/min @ 7 Bar
Operating Pressure	1 - 16 Bar
Operating Temperature	1,5 - 50 °C
Min. Service Interval	12 Months
Drain	Float Drain
Replacement Drain Element Part No.	17131042
Connection	3/8 BSPP Inch
LxWxH	65 x 76 x 311 mm
Weight	0.80 kg
Mounting Bracket Kit Part No.	17131085

- For the removal of bulk liquid, water and oil aerosols, atmospheric dirt and solid particles, rust, oil vapour, and micro-organisms
- Coalescing filter performance tested to the stringent requirements of ISO12500-1, ISO8573-2 and ISO8573-4
- Dry particulate filter performance tested in accordance with the requirements of ISO8573-4