

DATASHEET

Type of Valve	: 3/2 Spring Return Direct acting Universal Valve
Ordering Code	: 30334-5-2R-B9+III-24V-DC-39-H-01
Item Code	: 930000000099
Port Connection	: 1/4" NPT(F)
Orifice Size (mm)	: 5 mm
Flow Factor (kv)	: 8 LPM
Body Material	: Stainless Steel 316L with internal wetted parts of Stainless Steel 316L
Manual Override	: Manual Override Not Provided
Seat Seal Material	: NBR
Media	: Air, Clear Water
Main Pressure	: 0 - 10 bar
Media Temp Range	: -25°C to +75°C
Type of Solenoid	: Flameproof Enclosure Ex d having integrated Terminals, Horizontal Cable Entry M20X1.5mm (F)
Size of Coil	: III
Enclosure Material	: Aluminium Cast Epoxy Powder coated
Voltage	: 24V DC (-10%, +10%)
Power of Coil	: 8 W
Insulation Class	: Class H
Approval	: CE - ATEX
Coil Certificate nr.	: ATEX TI22ATEX 278X
Marking	: Ex II 2GD Ex db IIC T6/ T5 Gb Ex tb IIIC T80°C/ T95°C Db, IP66/ IP67 -40 °C < Ta < 60 °C FOR T6 -40 °C < Ta < 70 °C FOR T5
Created By: Sumit Rawat	Print Date And Time: 19/03/2026 20:19
This is System Generated Report	