



DOSATRON®

WATER POWERED DOSING TECHNOLOGY

14 GPM: D14MZ2

Product Specifications


Call 800-523-8499 to order the Dosatron for your specific application

Dilution Range:	1:500 to 1:50 (0.2% to 2%)
Water Flow Range:	0.05 to 14 GPM
Operating Pressure Range:	4.3 to 85 PSI
Available Housing Materials:	• Polypropylene (Standard Blue) • PVDF (White)
Dimensions:	19 1/18" x 6 5/16"
Weight:	6 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and operating manual
Recommended Accessories:	IPK34, Bypass - part #: MPDI196



Recommended Installation

IPK34 - 14 GPM Industrial Plumbing Kit



3/4" polypropylene Banjo single union ball valve
1/2" stainless steel ball valve
3/4" poly 200 mesh tee filter
3/4" brass pressure regulator w/gauge
3/4" 14 GPM flow restrictor
3/4" polypropylene check valve
3/4" union schedule 80 PVC
3/4" x 2" Banjo polypropylene fittings
1/2" x 2" Banjo polypropylene fittings
1/2" x 1/2" Banjo barb fitting
3/4" male to 1/2" female Banjo reducer bushing
3/4" Banjo T
3/4" Banjo street elbows
Roll of Teflon tape
Instruction card
Zip tie



Dosatron International
2090 Sunnydale Blvd. • Clearwater, FL, USA
800-523-8499 • www.dosatronusa.com

Dosatron International, Inc. is an industry leader in water-powered, proportional chemical injectors. Dosatron products are manufactured according to ISO 9001:2000 and ISO 14001:2004 standards.