




- Diamètre du corps : de 19 à 150 mm
- Course : de 7 à 125 mm
- Force : de 170 à 9500daN (9.5t)
- Taille très compacte
- Conception solide (sans soudure)




Type	Force daN	Course C mm	Référence	ISO	Pression MPa (bar)	Force F1 N*	Force F2 N*	LR mm	LC mm	Masse Kg
RGP	2400	16	443344/000-S		15 (150) (!)	23 860	36 120	77	61	1.50
		19	443345/000-S				36 560	83	64	1.54
		25	443346/000-S	X			37 370	95	70	1.66
		32	443347/000-S				37 810	109	77	1.78
		38	443348/000-S	X			38 200	121	83	1.88
		50	443349/000-S	X			38 630	145	95	2.10
		63	443350/000-S	X			38 920	171	108	2.30
		75	443351/000-S				39 110	195	120	2.50
		80	443352/000-S	X			39 140	205	125	2.60
		100	443353/000-S	X			39 360	245	145	2.90
		125	443354/000-S	X			39 460	295	170	3.30

* (N) = Kg $\times$ 9.80665 | (Kg)=N $\times$ 0.101972 | 1daN=1 $\times$ 101N | 1bar=1 $\times$ 10⁻¹MPa

Exemple de commande : RGP 2400 C50

Kit de rechange : 896533/000

Composition : bague de guidage, joints d'étanchéité, valve et lubrifiant.



(!) Une marque bleue est collée sur le ressort lorsque celui-ci est gonflé à une pression spéciale. (<15 MPa)

