



1PAAG9510GS PRESS RED VALVE PILOT OP, 1PAAG95-10G-S

[407AA01395A](#)

Model code: 1PAAG95-10G-S



Product specifications

| Characteristic          | Value                         | Description                        |
|-------------------------|-------------------------------|------------------------------------|
| Adjustment type         | LEAKPROOF SCREW               | Leakproof Screw                    |
| Brand                   | DANFOSS                       | Danfoss                            |
| Flow rate LPM           |                               | 14.000                             |
| Fluid compatibility     | MIL-H-5606, SAE10, SAE20, ETC | MIL-H-5606, SAE10, SAE20, etc      |
| Function                | PRESSURE REDUCING/RELIEVING   | Pressure Reducing/Relieving Valves |
| Housing                 | NO                            | No                                 |
| Installation type       | SCREW-IN CARTRIDGE            | Screw-in Cartridge                 |
| Leakage                 | 0.3 CC/MIN                    | 0.3 cc/min                         |
| Model Code 1            |                               | 1PAAG95-10G-S                      |
| Number of housing ports | 3                             | 3                                  |
| Operating temperature   | -30 C TO 90 C (-22 TO 194 F)  | -30 C to 90 C (-22 to 194 F)       |
| Operation               | PILOT OPERATED                | Pilot operated                     |
| Port size               | NONE                          | None                               |
| Port type               | CARTRIDGE ONLY                | Cartridge Only                     |
| Pressure rating BAR     |                               | 210.000                            |
| Product height in       |                               | 3.330                              |
| Product height mm       |                               | 84.582                             |
| Product length in       |                               | 4.960                              |
| Product length mm       |                               | 125.984                            |
| Product width in        |                               | 3.000                              |
| Product width mm        |                               | 76.200                             |



| Characteristic               | Value    | Description |
|------------------------------|----------|-------------|
| Recommended filtration level | 18/16/13 | 18/16/13    |
| Seal type                    | NITRILE  | Nitrile     |
| Special features             | NONE     | None        |
| Style                        | SPOOL    | Spool       |

