Machine foot H-US80-M24 x 231/118-M24 x 85, AISI 304, Black NBR



ARTICLE NUMBER 1000612

Type H US

The design and patent protected H US, H US Fixing & H US Double Fixing leveling foot is the acceptable choice for machinery and equipment that has to comply with hygienic requirements.

H61 US Fixing leveling foot is the acceptable choice for low-weight machinery and equipment that has to comply with hygienic requirements.

The thread is covered with a hygienic sleeve, which also functions as counter nut. All the movable parts are hygienically sealed.

Lowered cleaning effort is obtained by the design of the self-draining surfaces.

Additionally, the foot is hygienically sealed to the floor by vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate.

The H US Fixing, H US Double Fixing and H61 US Fixing is designed to be fastened to the floor by the fixing plate. Bolt, nut and washer can be supplied.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 069534	
Footplate diameter	80 mm	3.15”
Height adjustment	70 mm	2.76”
Height max.	208 mm	8.19”
Height min.	138 mm	5.43”
Height total	244 mm	9.61”
Mounting holes	0 Pieces	
Net weight	1209 g	
Nom. load	15000 N	3372.13lbs
Nom. pull	2500 N	562.02lbs
Rubber type	SH75A	
Sleeve diameter	24 mm	0.94”
Sleeve length	85 mm	3.35”
Spindle length	216.30 mm	8.52”
Thread diameter	24 mm	0.94”
Thread length	118 mm	4.65”
Thread size	M24	
Thread standard	Metric C	

Technical specifications

