

ROTEX AUTOMATION EUROPE

Address : Bierstraat 117, 3011 XA Rotterdam, The Netherlands

Website : www.rotexautomation.comE-mail : europe@rotexautomation.com*Engineering For The Future***DATASHEET**

Type of Valve	: 5/2 - 3/2 Convertible Spring Return Internal Pilot Operated Single Solenoid Namur Valve
Ordering Code	: 51450V02-6-2G-B5-S2G+III-24V-AC/DC-17-FR-02
Item Code	: 93000042261
Port Connection	: 1/4" BSP(F)
Orifice Size (mm)	: 6 mm
Flow Factor (kv)	: 12 LPM
Body Material	: Stainless Steel 316 with internal wetted parts of Stainless Steel 316
Manual Override	: Manual Override Provided Push to operate momentarily, for stayput using Screw Driver push & turn CW to operate valve
Seat Seal Material	: VITON GLT
Media	: Air;
Main Pressure	: 2 - 10 bar
Media Temp Range	: -40°C to +160°C
Type of Solenoid	: Weather Proof Enclosure having integral Terminals, Bottom Cable Entry M25X1.5(F)
Size of Coil	: III
Enclosure Material	: Aluminium Cast Powder coated
Special Version	: Inbuilt Full Rectifier with Surge Suppressor
Voltage	: 24V 50Hz/ 60Hz/ DC (-20%, +20%)
Power of Coil	: 8 W
Insulation Class	: Class H
Approval	: UL Recognised, for USA and Canada, Type 3, 3S, 4, 4X, 6, 6P UL file Number E 342217
Coil Certificate nr.	: 20171222-E342217 as per UL 429 & CAN/CSA C22.2 No. 139
Marking	: TYPE 3, 3R, 3S, 4, 4X, 6 & 6P -60°C to +100°C POWER ≤ 20W -60°C to +60°C 20W < POWER ≤ 30W
Created By: Sumit Rawat	Print Date And Time: 03/07/2026 20:45
This is System Generated Report	

Rotex Automation Europe is a registered trademark of Rotex Controls B.V.

Rotex Controls B.V. - VAT nr. NL819933259B01

Trade reg : 24443687 Rotterdam

Bankers : ABN Amro : 59.69.83.441 - IBAN : NL34ABNA0596983441 - BIC : ABN ANL 2A.

Phone : + 31 88 505 3 505