



WAMGROUP S.p.A.
Via Cavour 338
41030 Ponte Motta di Cavezzo (Modena) Italy
Tel. +39 0535 618 111 Fax +39 0535 618 226



PB FILTER MEDIA DATA SHEET

Certificate No.: 180824 PB Filter media Data
Sheet
Page 1/1

Product Name	P B POLYESTER SPUN BOND
Filter material	100% Polyester
Construction / Treatment	Polyester spun bond + antistatic finishing
Weight [g/m ²] – DIN EN 29073-1	235
Thickness [mm] – DIN EN ISO 9073-2	0.55
MD Tensile Strenght [N / 5cm] – DIN EN 29073-3	750
CD Tensile Strenght [N / 5cm] – DIN EN 29073-3	630
MD Elongation [%]	n.a.
CD Elongation [%]	n.a.
Air Permeability [l/dm ² min] @ 200 Pa – DIN EN ISO 9237	108
Temperature Resistance [°C]	120
Surface Resistance [Ω] – DIN 54345-1	< 10 ⁸
IFA Class	M

Efficiency certification IFA accredited.

Please contact WAMGROUP team for any information of range for EU and FDA certified product.

Ponte Motta di Cavezzo, August 24th, 2018
WAMGROUP S.p.A. – Dust Collectors Division dept.

Please note, values given may be subject to change without notice.

Please consult WAMGROUP before using these values for design or specification.